


STREAMJETBAR


www.tungaloy.com

Tungaloy Report No. 357-G

Highly rigid internal toolholders
with excellent chip evacuation



INDUSTRY 4.0
FEED the SPEED!



ACCELERATED MACHINING

TurnLine

STREAMJETBAR
TUNGALOY



Now available with new DPMT series for improved chatter stability

www.tungaloy.com

Engineered for tool strength and optimal chip evacuation


Tool body of special alloy steel, designed to reduce chatter !

- Ensures superior surface finish quality over conventional ID turning tools !
- Improved tool life, efficiency, and economy !



Optimal holder design assures low cutting load and high performance in the smallest bore diameters !

Cutting load comparison




Toolholder : A16Q-SDUPL07-D220
 Insert : DPMT070204-PS
 Workpiece material : S55C / C55
 Cutting speed : $V_c = 150$ m/min
 Coolant : Wet

Cutting load is reduced by 10% than conventional tool !

New DPMT insert with 11° flank clearance helps reduce cutting load !



Excellent performance for small diameter machining operations

- Minimum bore diameter from $\varnothing 4.5$ mm
- Steel and carbide shank available
- Straight shank type available
- Can be used with internal coolant supply
- Well designed chip pocket for excellent chip evacuation
- Easy to adjust overhang due to marked scale on shank
- Improved rigidity for minimizing bar deflection and chatter by FEM (Finite Element Method)
- Added Z cutting edge style for back boring




Applicable for a wide variety of machines

- Applicable sleeve for a variety of small lathes
- Supplied with Seal cap (optional)
- Suitably designed sleeve for directed external coolant flow (see picture below)




Stable tool life and excellent chip control

- W08 type chipbreaker
- Superior cutting edge due to fine grain carbide grade
- Two grades of inserts: **SH730** (for general purpose), TH10 (for non-ferrous)
- Expansion of corner R0.1 spec on "EPGT04" and "WBG03" insert types



Finite Analysis of the load transition



Increased rigidity for minimizing bar deflection and chatter

Rigidity comparison with a conventional boring bar (Illustrations)


The rigidity of the bar in the direction of the principal force is maximized because the thickest portion of the head is located as close as possible to the cutting edge.

Note: Load 1000N ($V_c = 150$ m/min, $a_p = 1.5$ mm, $f = 0.2$ mm/rev are assumed)
A16Q-STUPR13-D180

Large head design provides both high rigidity and good chip evacuation.





About 20% reduction in deflection compared with conventional bar



New pocket design for excellent chip evacuation

Cutting performance

The excellent chip evacuation minimizes tool failure caused by re-cutting chips and poor chip control. Damage to the work surface from chips is also eliminated.



The oil hole is positioned as close as possible to the cutting edge to ensure fluid is fed directly to the cutting point.


- Oil hole design

Distance between the cutting edge and the oil hole is minimized.
(Distance is reduced by 50% compared to existing boring bars.)

- Screw for oil hole*

- In the case of not using the oil hole, a special screw can be inserted to prevent chip coiling (optional).



* Negative type only



Improved tool life


By supplying the optimum level of cutting fluid, flank wear and rake face wear are suppressed, considerably improving tool life.

Toolholder : A16Q-STUPR1103-D180
Insert : TPMT110304-PS (GT730)
Work material : S45C (220HB)
: Boring (ø30 ~ 50 mm)
Cutting speed : $V_c = 100$ m/min
Depth of cut : $a_p = 0.5$ mm
Feed : $f = 0.2$ mm/rev
Cutting fluid : Water soluble type



Easy to use

Marking specifications



Applicable clamping screw

Cat. No. (Positive type only)

If screw is missing this detail simplifies locating a replacement with Cat. No.

Scale of overhang length

Useful for easy setting of the toolholder.

Tool holder Cat. No.

The minimum bore diameter is indicated in the Cat. No. The three-digit number at the end of the text indicates the minimum bore diameter.
(Example)-D140 → 14.0 mm

Applicable insert Cat. No.

Can identify the insert size and relief angle at a glance. Simplified tool management.

Carbide shank type

Combination of the highly rigid carbide shank and the head geometry can increase the tool rigidity and improve chip evacuation.



Guide to L/D

Steel shank	Carbide shank
$L/D \leq 3$	$L/D \leq 5$

(Note) L : Overhang length, D: Shank diameter

- For precision boring

- The increased rigidity suppresses chatter, producing excellent surface finishes.
- Excellent chip evacuation minimizes damage to the surface caused by chip re-cutting. This further improves surface finish.

DESIGNATION SYSTEM FOR TAC BORING TOOLHOLDERS

P		Screw-on type	C		Rhombic 80°	Symbol	Style	Offset	G		with	S		with	C	
			D		Rhombic 55°	A		without	J		with	V		without		
S			E		Rhombic 75°	B		without	K		with	X*		with	B	
			T		Triangular	C		without	L		with	Y		with	N	
V			V		Rhombic 35°	D		without	N		without	Z		without	P	
			Y		Y-shape Rhombic 25° (Tungaloy's symbol)	E		without	P*		without	Note: *mark-.Tungaloy Standard No mark: ISO standard				
W			W		Trigon	F		with	Q*		with					

A **12** **M** - **S** **T** **U** **P** **R** **1102** **D** **140**

1 Bar composition	2 Bar diameter
A Steel shank with oil hole	Bar diameter is shown in mm.
E Carbide shank with steel head and oil hole	

3 Toolholder length L ₁ (mm)
F 80
G 90
H 100
J 110
K 125
L 130
M 150
P 170
Q 180
R 200
S 250
T 300
U 350

8 Hand of tool	9 Insert size $\ell + (S)$
R	
L	











10 Min. bore. diameter
Stream Jet Bars
140 $\phi 14.0$ mm

For M, S, and C types conformed to ISO
"In ISO metric system, a two digit number indicates the edge length (ℓ) of the insert to be used in mm. If the insert thickness is different for the same edge length, add the thickness symbol (s) (two digit number)."
In above example, TP□□1102□□ ℓ S










10 Min. bore. diameter
Stream Jet Bars
140 $\phi 14.0$ mm

LIST OF STREAM JET BARS A wide range of styles and sizes available







Positive type

Style	Shank type	Shank diameter	Minimum bore diameter (mm)					
			0	10	20	30	40	50
 SEXPR/L P.13,29 Boring and facing Insert type: EP□□	Steel Carbide	ø4 ~ ø8 ø4 ~ ø8	ø4.5 — ø7 ø4.5 — ø7					
 SCLCR/L P.12,13 Boring and facing Insert type: CC□□	Steel Carbide	ø4 ~ ø25 ø4 ~ ø25	ø5 — ø27 ø5 — ø27					
 SWUBR/L P.27 Boring Insert type: WB□□	Steel Carbide	ø5 ~ ø8 ø5 ~ ø8	ø6 — ø8 ø6 — ø8					
 STUPR/L P.22,23 Boring Insert type: TP□□	Steel Carbide	ø7 ~ ø32 ø7 ~ ø25	ø8 — ø34 ø8 — ø27					
 STFPR/L P.21 Boring Insert type: TP□□	Steel Carbide	ø8 ~ ø25 ø8 ~ ø20	ø10 — ø27 ø10 — ø22					
 SCLPR/L P.14 Through boring Insert type: CP□□	Steel Carbide	ø8 ~ ø25 ø8 ~ ø16	ø10 — ø27 ø10 — ø20					
 STFBR/L P.20 Boring Insert type: SP□□	Steel Carbide	ø8 ~ ø25 ø8 ~ ø25	ø10 — ø27 ø10 — ø27					
 SSKPR/L P.19 Through boring Insert type: SP□□	Steel	ø16 ~ ø25		ø20 — ø31				
 SDUCR/L P.17 Internal profiling Insert type: DC□□	Steel Carbide	ø10 ~ ø25 ø10 ~ ø20	ø13 — ø32 ø13 — ø27					
 SDUPR/L P.18 Internal profiling Insert type: DC□□	Steel Carbide	ø12 ~ ø16 ø12 ~ ø16	ø15 — ø22 ø15 — ø22					
 SDQCR/L P.15 Internal profiling Insert type: VC□□	Steel Carbide	ø12 ~ ø16 ø12 ~ ø16	ø13 — ø30 ø13 — ø25					
 SDQPR/L P.16 Internal profiling Insert type: VB□□	Steel Carbide	ø12 ~ ø16 ø12 ~ ø16	ø15 — ø22 ø15 — ø22					
 SVUCR/L P.26 Internal profiling Insert type: DC□□	Steel Carbide	ø12 ~ ø40 ø12 ~ ø25	ø16 — ø50 ø18 — ø32					
 SVUBR/L P.25 Internal profiling Insert type: DC□□	Steel Carbide	ø16 ~ ø25 ø16 ~ ø25	ø20 — ø32 ø24.5 — ø34					

Positive type


Style	Shank type	Shank diameter	Minimum bore diameter (mm)						
			0	10	20	30	40	50	
 SVQCR/L P.25 Internal profiling Insert type: VC□□	Steel Carbide	ø10~ ø40 ø10~ ø16		ø13.5 ø13.5	 ø21.5 ø50				
 SVQBR/L P.24 Internal profiling Insert type: VB□□	Steel Carbide	ø12 ~ ø25 ø12 ~ ø25		ø17 ø17	 ø30.5 ø30.5				
 SDZCR/L P.19 Internal retracting Insert type: DC□□	Steel Carbide	ø12 ~ ø25 ø12 ~ ø16		ø14 ø18	 ø25 ø22				
 SVZCR/L P.27 Internal retracting Insert type: VC□□	Steel	ø12		ø16					
 SVZBR/L P.26 Internal retracting Insert type: VB□□	Steel	ø16 ~ ø32		ø20	 ø40				
 SEZPR/L P.28 Internal retracting Insert type: EP□□	Steel Carbide	ø4 ~ ø5 ø4 ~ ø5	ø5.5 ø5.5	ø6.5 ø6.5					
 SVJCR/L P.29,30 Internal sphere cutting Insert type: VC□□	Steel	ø12 ~ ø16		ø16	 ø20				
 SVJBR/L P.28,30 Internal sphere cutting Insert type: VB□□	Steel	ø20 ~ ø25			ø25	 ø30			
 SYQBR/L P.31 Internal undercut and profiling Insert type: YW□□	Steel Carbide	ø12 ~ ø16 ø12 ~ ø16		ø17 ø17	 ø21.5 ø21.5				
 SYUBR/L P.31 Internal profiling Insert type: YW□□	Steel Carbide	ø16 ø12 ~ ø16		ø20 ø20	 ø24.5				

Negative type

Style	Shank type	Shank diameter	Minimum bore diameter (mm)									
			0	10	20	30	40	50	60	70		
 PTUNR/L P.35 Boring Insert type: TN□□	Steel	ø16 ~ ø32			ø20		ø40					
 PTFNR/L P.35 Boring Insert type: TN□□	Steel	ø25 ~ ø50				ø32			ø63			
 PSKNR/L P.34 Through boring Insert type: SN□□	Steel	ø32 ~ ø50				ø40			ø63			
 PDUNR/L P.33 Internal profiling Insert type: DN□□	Steel	ø20 ~ ø50			ø25				ø63			
 PCLNR/L P.32 Boring and facing Insert type: CN□□	Steel	ø16 ~ ø50			ø20				ø63			
 PWLNR/L P.37 Boring and facing Insert type: WN□□	Steel	ø16 ~ ø40			ø20			ø50				
 PVUNR/L P.36 Internal profiling Insert type: VN□□	Steel	ø25 ~ ø40				ø37		ø50				
 PDZNR/L P.34 Internal retracting Insert type: DN□□	Steel	ø32 ~ ø50					ø40		ø63			

A/E-SCLCR/L

Screw-on boring bars, for positive 80° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	GAMP	GAMF	RE**	Insert	Torque*
A04F-SCLCR/L03-D050	STEEL	5	4	2.5	80	8	3.8	0	-15	0.2	CC**03X1...	0.6
A05F-SCLCR/L03-D060	STEEL	6	5	3	80	9	4.8	0	-13	0.2	CC**03X1...	0.6
A06G-SCLCR/L04-D070	STEEL	7	6	3.5	90	11	5.75	0	-13	0.2	CC**04T1...	0.6
A07G-SCLCR/L04-D080	STEEL	8	7	4	90	12	6.75	0	-11	0.2	CC**04T1...	0.6
A08H-SCLCR/L06-D100	STEEL	10	8	5.5	100	16	7.5	0	-13	0.4	CC**0602...	1.2
A10F-SCLCR06-D120	STEEL	12	10	6	80	20	9	0	-10	0.4	CC**0602...	1.2
A10K-SCLCR/L06-D120	STEEL	12	10	6	125	20	9	0	-10	0.4	CC**0602...	1.2
A12H-SCLCR06-D140	STEEL	14	12	7	100	24	11	0	-8	0.4	CC**0602...	1.2
A12M-SCLCR/L06-D140	STEEL	14	12	7	150	24	11	0	-8	0.4	CC**0602...	1.2
A12H-SCLCR06-D160	STEEL	16	12	9	100	24	11	0	-7	0.4	CC**0602...	1.2
A12M-SCLCR/L06-D160	STEEL	16	12	9	150	24	11	0	-7	0.4	CC**0602...	1.2
A16K-SCLCR09-D180	STEEL	18	16	9	125	32	15	0	-9	0.8	CC**09T3...	3
A16Q-SCLCR/L09-D180	STEEL	18	16	9	180	32	15	0	-10	0.8	CC**09T3...	3
A16K-SCLCR09-D200	STEEL	20	16	11	125	32	15	0	-9	0.8	CC**09T3...	3
A16Q-SCLCR/L09-D200	STEEL	20	16	11	180	32	15	0	-9	0.8	CC**09T3...	3
A20R-SCLCR/L09-D220	STEEL	22	20	11	200	32	18	0	-8	0.8	CC**09T3...	3
A25S-SCLCR/L09-D270	STEEL	27	25	13.5	250	45	23	0	-6	0.8	CC**09T3...	3
E04G-SCLCR/L03-D050	CARBIDE	5	4	2.5	90	9	3.8	0	-15	0.2	CC**03X1...	0.6
E05G-SCLCR/L03-D060	CARBIDE	6	5	3	90	10	4.8	0	-13	0.2	CC**03X1...	0.6
E06H-SCLCR/L04-D070	CARBIDE	7	6	3.5	100	12	5.75	0	-13	0.2	CC**04T1...	0.6
E07H-SCLCR/L04-D080	CARBIDE	8	7	4	100	14	6.75	0	-11	0.2	CC**04T1...	0.6
E08G-SCLCR06-D100	CARBIDE	10	8	5.5	90	22	7.5	0	-13	0.4	CC**0602...	1.2
E08K-SCLCR/L06-D100	CARBIDE	10	8	5.5	125	22	7.5	0	-13	0.4	CC**0602...	1.2
E10F-SCLCR06-D120	CARBIDE	12	10	6	80	25	9	0	-10	0.4	CC**0602...	1.2
E10H-SCLCR06-D120	CARBIDE	12	10	6	100	25	9	0	-10	0.4	CC**0602...	1.2
E10M-SCLCR/L06-D120	CARBIDE	12	10	6	150	25	9	0	-10	0.4	CC**0602...	1.2
E12G-SCLCR06-D140	CARBIDE	14	12	7	90	27	11	0	-8	0.4	CC**0602...	1.2
E12J-SCLCR06-D140	CARBIDE	14	12	7	110	27	11	0	-8	0.4	CC**0602...	1.2
E12Q-SCLCR/L06-D140	CARBIDE	14	12	7	180	27	11	0	-8	0.4	CC**0602...	1.2
E12G-SCLCR06-D160	CARBIDE	16	12	9	90	27	11	0	-7	0.4	CC**0602...	1.2
E12J-SCLCR06-D160	CARBIDE	16	12	9	110	27	11	0	-7	0.4	CC**0602...	1.2
E12Q-SCLCR/L06-D160	CARBIDE	16	12	9	180	27	11	0	-7	0.4	CC**0602...	1.2
E16H-SCLCR09-D180	CARBIDE	18	16	9	100	32	15	0	-10	0.8	CC**09T3...	3
E16L-SCLCR09-D180	CARBIDE	18	16	9	130	32	15	0	-10	0.8	CC**09T3...	3
E16R-SCLCR/L09-D180	CARBIDE	18	16	9	200	32	15	0	-10	0.8	CC**09T3...	3
E16H-SCLCR09-D200	CARBIDE	20	16	11	100	32	15	0	-9	0.8	CC**09T3...	3
E16L-SCLCR09-D200	CARBIDE	20	16	11	130	32	15	0	-9	0.8	CC**09T3...	3
E16R-SCLCR/L09-D200	CARBIDE	20	16	11	200	32	15	0	-9	0.8	CC**09T3...	3
E20S-SCLCR09-D220	CARBIDE	22	20	11	250	36	18	0	-8	0.8	CC**09T3...	3
E25T-SCLCR09-D270	CARBIDE	27	25	13.5	300	45	23	0	-6	0.8	CC**09T3...	3

*Torque: Recommended torque (N-m) for clamping **RE: Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SCLCL** type), and the left hand insert (L) is used for the right hand toolholders (SCLCR** type).


SPARE PARTS



Designation	Clamping screw	Wrench
A**-SCLCR/L03-D...	CSTA-1.6	T-6F
A**-SCLCR/L04-D...	CSTB-2	T-6F
A**-SCLCR/L06-D...	CSTB-2.5S	T-8F
A**-SCLCR/L09-D...	CSTB-4S	T-15F
E**-SCLCR/L03-D...	CSTA-1.6	T-6F
E**-SCLCR/L04-D...	CSTB-2	T-6F
E**-SCLCR/L06-D...	CSTB-2.5S	T-8F
E16*-SCLCR/L09-D...	CSTB-4L060	T-15F
E2**-SCLCR/L09-D...	CSTB-4S	T-15F

A/E-SEXPR/L

Screw-on boring bars, for positive 75° rhombic inserts



Cutting edge style X

Right hand (R) shown.

Designation	Material	DMIN	DCONMS	WF	LF	LH	H	GAMP	GAMF	RE**	Insert	Torque*
A04F-SEXPR/L03-D045	STEEL	4.5	4	2.3	80	8	3.8	0	-15	0.2	EP**03X1...	0.6
A04F-SEXPR/L03-D050	STEEL	5	4	2.5	80	8	3.8	0	-13	0.2	EP**03X1...	0.6
A05F-SEXPR/L04-D055	STEEL	5.5	5	2.75	80	9	4.8	0	-12	0.4	EP**0401...	0.6
A06G-SEXPR/L04-D070	STEEL	7	6	3.6	90	11	5.75	0	-12	0.4	EP**0401...	0.6
A08H-SEXPR/L04-D055	STEEL	5.5	8	2.75	100	16	7.5	0	-12	0.4	EP**0401...	0.6
A08H-SEXPR/L04-D070	STEEL	7	8	3.6	100	20	7.5	0	-12	0.4	EP**0401...	0.6
E04G-SEXPR/L03-D045	CARBIDE	4.5	4	2.3	90	9	3.8	0	-15	0.2	EP**03X1...	0.6
E04G-SEXPR/L03-D050	CARBIDE	5	4	2.5	90	9	3.8	0	-13	0.2	EP**03X1...	0.6
E05G-SEXPR/L04-D055	CARBIDE	5.5	5	2.75	90	10	4.8	0	-12	0.4	EP**0401...	0.6
E06H-SEXPR/L04-D070	CARBIDE	7	6	3.6	100	12	5.75	0	-12	0.4	EP**0401...	0.6
E08K-SEXPR/L04-D055	CARBIDE	5.5	8	2.75	125	28	7.5	0	-12	0.4	EP**0401...	0.6
E08K-SEXPR/L04-D070	CARBIDE	7	8	3.6	125	40	7.5	0	-12	0.4	EP**0401...	0.6

*Torque: Recommended torque (N·m) for clamping **_{re}: Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SEXPL** type), and the left hand insert (L) is used for the right hand toolholders (SEXPR** type).


SPARE PARTS



Designation	Clamping screw	Wrench
A**-SEXPR/L03-D...	CSTA-1.6	T-6F
A**-SEXPR/L04-D...	CSTB-2	T-6F
E**-SEXPR/L03-D...	CSTA-1.6	T-6F
E**-SEXPR/L04-D...	CSTB-2	T-6F

A/E-SCLPR/L

Screw-on boring bars, for positive 80° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	GAMP	GAMF	RE**	Insert	Torque*
A08H-SCLPR/L06-D100	STEEL	10	8	5.5	100	16	7.5	5	-8	0.4	CP**0602...	1.2
A10K-SCLPR/L06-D120	STEEL	12	10	6	125	20	9	5	-5	0.4	CP**0602...	1.2
A10K-SCLPR/L08-D120	STEEL	12	10	6	125	20	9	5	-5	0.4	CP**0802...	1.4
A12M-SCLPR/L06-D140	STEEL	14	12	7	150	24	11	5	-4	0.4	CP**0602...	1.2
A12M-SCLPR/L08-D140	STEEL	14	12	7	150	24	11	5	-4	0.4	CP**0802...	1.4
A12M-SCLPR/L08-D160	STEEL	16	12	9	150	24	11	5	-3	0.4	CP**0802...	1.4
A16Q-SCLPR/L09-D180	STEEL	18	16	9	180	32	15	5	-3.5	0.8	CP**0903...	3
A16Q-SCLPR/L09-D200	STEEL	20	16	11	180	32	15	5	-3	0.8	CP**0903...	3
A20R-SCLPR/L09-D220	STEEL	22	20	11	200	36	18	5	-2	0.8	CP**0903...	3
A25S-SCLPR/L09-D270	STEEL	27	25	13.5	250	45	23	5	-1	0.8	CP**0903...	3
E08K-SCLPR/L06-D100	CARBIDE	10	8	5.5	125	22	7.5	5	-8	0.4	CP**0602...	1.2
E10M-SCLPR/L06-D120	CARBIDE	12	10	6	150	25	9	5	-5	0.4	CP**0602...	1.2
E10H-SCLPR08-D120	CARBIDE	12	10	6	100	25	9	5	-5	0.4	CP**0802...	1.4
E10M-SCLPR/L08-D120	CARBIDE	12	10	6	150	25	9	5	-5	0.4	CP**0802...	1.4
E12Q-SCLPR/L06-D140	CARBIDE	14	12	7	180	27	11	5	-4	0.4	CP**0602...	1.2
E12G-SCLPR08-D140	CARBIDE	14	12	7	90	27	11	5	-4	0.4	CP**0802...	1.4
E12J-SCLPR08-D140	CARBIDE	14	12	7	110	27	11	5	-4	0.4	CP**0802...	1.4
E12Q-SCLPR/L08-D140	CARBIDE	14	12	7	180	27	11	5	-4	0.4	CP**0802...	1.4
E12G-SCLPR08-D160	CARBIDE	16	12	9	90	27	11	5	-3	0.4	CP**0802...	1.4
E12J-SCLPR08-D160	CARBIDE	16	12	9	110	27	11	5	-3	0.4	CP**0802...	1.4
E12Q-SCLPR/L08-D160	CARBIDE	16	12	9	180	27	11	5	-3	0.4	CP**0802...	1.4
E16H-SCLPR09-D180	CARBIDE	18	16	9	100	32	15	5	-3.5	0.8	CP**0903...	3
E16L-SCLPR09-D180	CARBIDE	18	16	9	130	32	15	5	-3.5	0.8	CP**0903...	3
E16R-SCLPL09-D180	CARBIDE	18	16	9	200	32	15	5	-3.5	0.8	CP**0903...	3
E16H-SCLPR09-D200	CARBIDE	20	16	11	100	32	15	5	-3	0.8	CP**0903...	3
E16L-SCLPR09-D200	CARBIDE	20	16	11	130	32	15	5	-3	0.8	CP**0903...	3
E16R-SCLPL09-D200	CARBIDE	20	16	11	200	32	15	5	-3	0.8	CP**0903...	3

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SCLPL** type), and the left hand insert (L) is used for the right hand toolholders (SCLPR** type).

SPARE PARTS

Designation	Clamping screw	Wrench
A**-SCLPR/L06-D...	CSTB-2.5S	T-8F
A10K-SCLPR/L08-D120	CSTB-3L042	T-9F
A12M-SCLPR/L08-D...	CSTB-3L050	T-9F
A**-SCLPR/L09-D...	CSTB-4L060	T-15F
E**-SCLPR/L06-D...	CSTB-2.5S	T-8F
E10*-SCLPR/L08-D...	CSTB-3L042	T-9F
E12*-SCLPR/L08-D...	CSTB-3L050	T-9F
E16*-SCLPR/L09-D...	CSTB-4L060	T-15F

A/E-SDQCR/L

Screw-on boring bars, for positive 55° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f ₂	GAMF	GAMF	RE**	Insert	Torque*
A10K-SDQCR/L07-D130	STEEL	13	10	7.6	125	20	9	2.6	0	-8	0.4	DC**0702...	1.2
A12M-SDQCR/L07-D160	STEEL	16	12	8.6	150	24	11	2.6	0	-6	0.4	DC**0702...	1.2
A16Q-SDQCR/L07-D200	STEEL	20	16	10.6	180	32	15	2.6	0	-5	0.4	DC**0702...	1.2
A20R-SDQCR/L11-D250	STEEL	25	20	13.7	200	36	18	3.7	0	-7	0.8	DC**11T3...	3
A25S-SDQCR/L11-D300	STEEL	30	25	16.2	250	45	23	3.7	0	-4	0.8	DC**11T3...	3
E10H-SDQCR07-D130	CARBIDE	13	10	7.6	100	25	9	2.5	0	-8	0.4	DC**0702...	1.2
E10M-SDQCR/L07-D130	CARBIDE	13	10	7.6	150	25	9	2.6	0	-8	0.4	DC**0702...	1.2
E12J-SDQCR07-D160	CARBIDE	16	12	8.6	110	27	11	2.5	0	-6	0.4	DC**0702...	1.2
E12Q-SDQCR/L07-D160	CARBIDE	16	12	8.6	180	27	11	2.6	0	-6	0.4	DC**0702...	1.2
E16L-SDQCR07-D200	CARBIDE	20	16	10.6	130	32	15	2.5	0	-5	0.4	DC**0702...	1.2
E16R-SDQCR/L07-D200	CARBIDE	20	16	10.6	200	32	15	2.6	0	-5	0.4	DC**0702...	1.2
E20S-SDQCR/L11-D250	CARBIDE	25	20	13.7	250	36	18	3.7	0	-7	0.8	DC**11T3...	3

*Torque: Recommended torque (N·m) for clamping **RE:Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SDQCL** type), and the left hand insert (L) is used for the right hand toolholders (SDQCR** type).

SPARE PARTS




Designation	Clamping screw	Wrench
A1**-SDQCR/L07-D**0	CSTB-2.5S	T-8F
A2**-SDQCR/L11-D**0	CSTB-4S	T-15F
E1**-SDQCR/L07-D**0	CSTB-2.5S	T-8F
E20S-SDQCR/L11-D250	CSTB-4S	T-15F


A/E-SDQPR/L

Screw-on boring bars, for Posi 55deg rhombic insert with 11 deg clearance

New



Cutting edge style Q



Right hand (R) shown.

Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A12M-SDQPR07-D150-P	SPECIAL ALLOY STEEL	15	12	8.3	150	24	11	2.3	5	0	0.40	DPMT0702...	1.2
A12M-SDQPL07-D150-P	SPECIAL ALLOY STEEL	15	12	8.3	150	24	11	2.3	5	0	0.40	DPMT0702...	1.2
A12M-SDQPR07-D180-P	SPECIAL ALLOY STEEL	18	12	9.6	150	24	11	3.6	5	0	0.40	DPMT0702...	1.2
A12M-SDQPL07-D180-P	SPECIAL ALLOY STEEL	18	12	9.6	150	24	11	3.6	5	0	0.40	DPMT0702...	1.2
A16Q-SDQPR07-D220-P	SPECIAL ALLOY STEEL	22	16	11.6	180	32	15	3.6	5	0	0.40	DPMT0702...	1.2
A16Q-SDQPL07-D220-P	SPECIAL ALLOY STEEL	22	16	11.6	180	32	15	3.6	5	0	0.40	DPMT0702...	1.2
E12Q-SDQPR07-D150	CARBIDE	15	12	8.3	180	27	11	2.3	5	0	0.40	DPMT0702...	1.2
E12Q-SDQPL07-D150	CARBIDE	15	12	8.3	180	27	11	2.3	5	0	0.40	DPMT0702...	1.2
E12Q-SDQPR07-D180	CARBIDE	18	12	9.6	180	27	11	3.6	5	0	0.40	DPMT0702...	1.2
E12Q-SDQPL07-D180	CARBIDE	18	12	9.6	180	27	11	3.6	5	0	0.40	DPMT0702...	1.2
E16R-SDQPR07-D220	CARBIDE	22	16	11.6	200	32	15	3.6	5	0	0.40	DPMT0702...	1.2
E16R-SDQPL07-D220	CARBIDE	22	16	11.6	200	32	15	3.6	5	0	0.40	DPMT0702...	1.2

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SDQCL** type), and the left hand insert (L) is used for the right hand toolholders (SDQCR** type).


SPARE PARTS



Designation	Clamping screw	Wrench
A**-SDQPR/L07-D**0-P	CSTB-2.5S	T-8F
E**-SDQPR/L07-D**0	CSTB-2.5S	T-8F

A/E-SDUCR/L

Screw-on boring bars, for positive 55° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f ₂	GAMP	GAMF	RE**	Insert	Torque*
A10K-SDUCR/L07-D130	STEEL	13	10	7	125	20	9	2	0	-10	0.4	DC**0702...	1.2
A12M-SDUCR/L07-D160	STEEL	16	12	9.3	150	24	11	3.3	0	-6	0.4	DC**0702...	1.2
A16Q-SDUCR/L07-D200	STEEL	20	16	11.3	180	32	15	3.3	0	-5	0.4	DC**0702...	1.2
A20R-SDUCR/L11-D270	STEEL	27	20	16.1	200	36	18	6.1	0	-5	0.8	DC**11T3...	3
A25S-SDUCR/L11-D320	STEEL	32	25	18.6	250	45	23	6.1	0	-4	0.8	DC**11T3...	3
E10H-SDUCR07-D130	CARBIDE	13	10	7	100	25	9	1.9	5	-3.5	0.4	DC**0702...	1.2
E10M-SDUCR/L07-D130	CARBIDE	13	10	7	150	25	9	2	0	-10	0.4	DC**0702...	1.2
E12J-SDUCR07-D160	CARBIDE	16	12	9.3	110	27	11	3.2	0	-6	0.4	DC**0702...	1.2
E12Q-SDUCR/L07-D160	CARBIDE	16	12	9.3	180	27	11	3.3	0	-6	0.4	DC**0702...	1.2
E16L-SDUCR07-D200	CARBIDE	20	16	11.3	130	32	15	3.2	0	-5	0.4	DC**0702...	1.2
E16R-SDUCR/L07-D200	CARBIDE	20	16	11.3	200	32	15	3.3	0	-5	0.4	DC**0702...	1.2
E20S-SDUCR11-D270	CARBIDE	27	20	16.1	250	36	18	6.1	0	-5	0.8	DC**11T3...	3

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SDUCL** type), and the left hand insert (L) is used for the right hand toolholders (SDUCR** type).

SPARE PARTS




Designation	Clamping screw	Wrench
A1**-SDUCR/L07-D1*0	CSTB-2.5S	T-8F
A16Q-SDUCR/L07-D200	CSTB-2.5	T-8F
A2**-SDUCR/L11-D**0	CSTB-4S	T-15F
E1**-SDUCR/L07-D1*0	CSTB-2.5S	T-8F
E16*-SDUCR/L07-D200	CSTB-2.5	T-8F
E20S-SDUCR11-D270	CSTB-4S	T-15F


A/E-SDUPR/L

Screw-on boring bars, for Posi 55deg rhombic insert with 11 deg clearance

New



Cutting edge style U



Right hand (R) shown.

Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A12M-SDUPR07-D150-P	SPECIAL ALLOY STEEL	15	12	8.3	150	24	11	2.3	5	0	0.4	DPMT0702**-PS	1.2
A12M-SDUPL07-D150-P	SPECIAL ALLOY STEEL	15	12	8.3	150	24	11	2.3	5	0	0.4	DPMT0702**-PS	1.2
A12M-SDUPR07-D180-P	SPECIAL ALLOY STEEL	18	12	10.3	150	24	11	4.3	5	0	0.4	DPMT0702**-PS	1.2
A12M-SDUPL07-D180-P	SPECIAL ALLOY STEEL	18	12	10.3	150	24	11	4.3	5	0	0.4	DPMT0702**-PS	1.2
A16Q-SDUPR07-D220-P	SPECIAL ALLOY STEEL	22	16	12.3	180	32	15	4.3	5	0	0.4	DPMT0702**-PS	1.2
A16Q-SDUPL07-D220-P	SPECIAL ALLOY STEEL	22	16	12.3	180	32	15	4.3	5	0	0.4	DPMT0702**-PS	1.2
E12Q-SDUPR07-D150	CARBIDE	15	12	8.3	180	27	11	2.3	5	0	0.4	DPMT0702**-PS	1.2
E12Q-SDUPL07-D150	CARBIDE	15	12	8.3	180	27	11	2.3	5	0	0.4	DPMT0702**-PS	1.2
E12Q-SDUPR07-D180	CARBIDE	18	12	10.3	180	27	11	4.3	5	0	0.4	DPMT0702**-PS	1.2
E12Q-SDUPL07-D180	CARBIDE	18	12	10.3	180	27	11	4.3	5	0	0.4	DPMT0702**-PS	1.2
E16R-SDUPR07-D220	CARBIDE	22	16	12.3	200	32	15	4.3	5	0	0.4	DPMT0702**-PS	1.2
E16R-SDUPL07-D220	CARBIDE	22	16	12.3	200	32	15	4.3	5	0	0.4	DPMT0702**-PS	1.2

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SDUCL** type), and the left hand insert (L) is used for the right hand toolholders (SDUCR** type).


SPARE PARTS



Designation	Clamping screw	Wrench
A**-SDUPR/L07-D**0-P	CSTB-2.5S	T-8F
E**-SDUPR/L07-D**0	CSTB-2.5S	T-8F

A/E-SDZCR/L

Screw-on boring bars, for positive 55° rhombic inserts



Cutting edge style Z

Right hand (R) shown.

Designation	Material	DMIN	DCONMS	WF	LF	LH	L3	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A12M-SDZCR/L07-D140	STEEL	14	12	10.5	150	30	12.5	11	4.5	0	-9	0.4	DC**0702...	1.2
A16Q-SDZCR/L07-D160	STEEL	16	16	12.5	180	35	12.5	15	4.5	0	-8	0.4	DC**0702...	1.2
A20R-SDZCR/L11-D200	STEEL	20	20	15.5	200	40	15.0	18	5.5	0	-8	0.8	DC**11T3...	3
A25S-SDZCR/L11-D250	STEEL	25	25	18	250	50	15	23	5.5	0	-6	0.8	DC**11T3...	3
E12Q-SDZCR/L07-D180	CARBIDE	18	12	10.5	180	-	12.5	11	4.5	0	-8	0.4	DC**0702...	1.2
E16R-SDZCR/L07-D220	CARBIDE	22	16	12.5	200	-	12.5	15	4.5	0	-6	0.4	DC**0702...	1.2

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the right hand toolholders (SDZCR ** type), and the left hand insert (L) is used for the left hand toolholders (SDZCL ** type).


SPARE PARTS



Designation	Clamping screw	Wrench
A1**-SDZCR/L07-D1*0	CSTB-2.5	T-8F
A2**-SDZCR/L11-D2*0	CSTB-4S	T-15F
E1**-SDZCR/L07-D**0	CSTB-2.5	T-8F

A-SSKPR

Screw-on boring bars, for positive square inserts



Cutting edge style K

Right hand (R) shown.

Designation	Material	DMIN	DCONMS	WF	LF	LH	H	GAMP	GAMF	RE**	Insert	Torque*
A16Q-SSKPR09-D200	STEEL	20	16	11	180	32	15	5	-6	0.8	SP**0903...	3
A20R-SSKPR09-D240	STEEL	24	20	13	200	36	18	5	-2	0.8	SP**0903...	3
A25S-SSKPR12-D310	STEEL	31	25	17	250	45	23	5	-2	0.8	SP**1204...	6

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SSKPL** type), and the left hand insert (L) is used for the right hand toolholders (SSKPR** type).


SPARE PARTS



Designation	Clamping screw	Wrench
A**-SSKPR09-D2*0	CSTB-4L060	T-15F
A25S-SSKPR12-D310	CSTB-5S	T-20F

A/E-STFCR/L

Screw-on boring bars, for positive triangle inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f ₂	GAMP	GAMF	RE**	Insert	Torque*
A10K-STFCR/L1103-D120	STEEL	12	10	6.5	125	20	9	0.6	0	-13	0.4	TC**1103...	1.2
A12M-STFCR/L1103-D140	STEEL	14	12	7	150	24	11	0.5	0	-10	0.4	TC**1103...	1.2
A16Q-STFCR/L1103-D180	STEEL	18	16	9	180	32	15	0.5	0	-7	0.4	TC**1103...	1.2
E10M-STFCR/L1103-D120	CARBIDE	12	10	6.5	150	25	9	0.7	0	-13	0.4	TC**1103...	1.2
E12Q-STFCR/L1103-D140	CARBIDE	14	12	7	180	27	11	0.5	0	-10	0.4	TC**1103...	1.2
E16R-STFCR/L1103-D180	CARBIDE	18	16	9	200	32	15	0.5	0	-7	0.4	TC**1103...	1.2

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (STFCL** type), and the left hand insert (L) is used for the right hand toolholders (STFCR** type).


SPARE PARTS



Designation	Clamping screw	Wrench
A**-STFCR/L1103-D...	CSTB-2.5	T-8F
E**-STFCR/L1103-D...	CSTB-2.5	T-8F

A/E-STFPR/L

Screw-on boring bars, for positive triangle inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A08H-STFPR/L09-D100	STEEL	10	8	5.5	100	16	7.5	0.7	5	-8	0.4	TP**0902...	0.9
A10K-STFPR/L1102-D120	STEEL	12	10	6.5	125	20	9	0.7	5	-6	0.4	TP**1102...	1.2
A12M-STFPR/L1102-D140	STEEL	14	12	7.0	150	24	11	0.6	5	-4	0.4	TP**1102...	1.2
A16Q-STFPR/L13-D180	STEEL	18	16	9	180	32	15	0.7	5	-2	0.4	TP**1303...	1.4
A20R-STFPR13-D220	STEEL	22	20	11	200	36	18	0.8	5	-2	0.4	TP**1303...	1.4
A25S-STFPR16-D270	STEEL	27	25	13.5	250	45	23	0.6	5	-1	0.4	TP**16T3...	3
E08K-STFPR/L09-D100	CARBIDE	10	8	5.5	125	22	7.5	0.7	5	-8	0.4	TP**0902...	0.9
E10M-STFPR/L1102-D120	CARBIDE	12	10	6.5	150	25	9	0.7	5	-6	0.4	TP**1102...	1.2
E12Q-STFPR/L1102-D140	CARBIDE	14	12	7	180	27	11	0.6	5	-4	0.4	TP**1102...	1.2
E16R-STFPR13-D180	CARBIDE	18	16	9	200	32	15	0.7	5	-2	0.4	TP**1303...	1.4
E20S-STFPR13-D220	CARBIDE	22	20	11	250	36	18	0.8	5	-2	0.4	TP**1303...	1.4

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (STFPL ** type), and the left hand insert (L) is used for the right hand toolholders (STFPR ** type).

(1) Inserts of TPGH, TPGM and TPGA are not applicable.


SPARE PARTS



Designation	Clamping screw	Wrench
A08H-STFPR/L09-D100	CSTB-2.2S	T-7F
A10K-STFPR/L1102-D120	CSTB-2.5B	T-8F
A12M-STFPR/L1102-D140	CSTB-2.5	T-8F
A16Q-STFPR/L13-D180	CSTB-3S	T-9F
A20R-STFPR13-D220	CSTB-3	T-9F
A25S-STFPR16-D270	CSTB-4M	T-15F
E08K-STFPR/L09-D100	CSTB-2.2S	T-7F
E10M-STFPR/L1102-D120	CSTB-2.5B	T-8F
E12Q-STFPR/L1102-D140	CSTB-2.5	T-8F
E16R-STFPR13-D180	CSTB-3S	T-9F
E20S-STFPR13-D220	CSTB-3	T-9F

A/E-STUPR/L

Screw-on boring bars, for positive triangle inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A07G-STUPR/L07-D080	STEEL	8	7	4	90	12	6.75	0.4	5	-10	0.4	TP**0701...	0.9
A08H-STUPR/L07-D080	STEEL	8	8	4	100	19.5	7.5	0.5	5	-10	0.4	TP**0701...	0.9
A08H-STUPR/L09-D100	STEEL	10	8	5.5	100	16	7.5	0.6	5	-8	0.4	TP**0902... ⁽¹⁾	0.9
A10F-STUPR1102-D120	STEEL	12	10	6.5	80	20	9	1.4	5	-6	0.4	TP**1102... ⁽¹⁾	1.2
A10K-STUPR/L1102-D120	STEEL	12	10	6.5	125	20	9	0.7	5	-6	0.4	TP**1102... ⁽¹⁾	1.2
A10K-STUPR/L1103-D120	STEEL	12	10	6.5	125	20	9	0.6	5	-10	0.4	TP**1103... ⁽¹⁾	1.4
A12H-STUPR1102-D140	STEEL	14	12	7	100	24	11	0.8	5	-4	0.4	TP**1102... ⁽¹⁾	1.2
A12M-STUPR/L1102-D140	STEEL	14	12	7	150	24	11	0.8	5	-4	0.4	TP**1102... ⁽¹⁾	1.2
A12M-STUPR/L1103-D140	STEEL	14	12	7	150	24	11	0.6	5	-6	0.4	TP**1103... ⁽¹⁾	1.4
A12H-STUPR1102-D160	STEEL	16	12	9	100	24	11	0.6	5	-3	0.4	TP**1102... ⁽¹⁾	1.2
A12M-STUPR/L1102-D160	STEEL	16	12	9	150	24	11	0.6	5	-3	0.4	TP**1102... ⁽¹⁾	1.2
A16K-STUPR13-D180	STEEL	18	16	9	125	32	15	0.8	5	-3	0.4	TP**1303... ⁽¹⁾	1.4
A16Q-STUPR/L1103-D180	STEEL	18	16	9	180	32	15	0.8	5	-4	0.4	TP**1103... ⁽¹⁾	1.4
A16Q-STUPR/L13-D180	STEEL	18	16	9	180	32	15	0.8	5	-3	0.4	TP**1303... ⁽¹⁾	1.4
A16K-STUPR13-D200	STEEL	20	16	11	125	32	15	0.6	5	-3	0.4	TP**1303... ⁽¹⁾	1.4
A16Q-STUPR/L13-D200	STEEL	20	16	11	180	32	15	0.6	5	-3	0.4	TP**1303... ⁽¹⁾	1.4
A20R-STUPR/L1103-D220	STEEL	22	20	11	200	36	18	0.7	5	-2	0.4	TP**1103... ⁽¹⁾	1.4
A20R-STUPR/L13-D220	STEEL	22	20	11	200	36	18	0.7	5	-2	0.4	TP**1303... ⁽¹⁾	1.4
A25S-STUPR/L16-D270	STEEL	27	25	13.5	250	45	23	0.5	5	-1	0.8	TP**16T3... ⁽¹⁾	3
A32T-STUPR/L16-D340	STEEL	34	32	17	300	50	30	0.7	5	0	0.8	TP**16T3...	3
E07H-STUPR/L07-D080	CARBIDE	8	7	4	100	14	6.75	0.3	5	-10	0.4	TP**0701...	0.9
E08G-STUPR07-D080	CARBIDE	8	8	4	90	44.5	7.5	0.5	5	-10	0.4	TP**0701...	0.9
E08K-STUPR/L07-D080	CARBIDE	8	8	4	125	44.5	7.5	0.5	5	-10	0.4	TP**0701...	0.9
E08G-STUPR09-D100	CARBIDE	10	8	5.5	90	22	7	0.6	5	-8	0.4	TP**0902... ⁽¹⁾	0.9
E08K-STUPR/L09-D100	CARBIDE	10	8	5.5	125	22	7	0.6	5	-8	0.4	TP**0902... ⁽¹⁾	0.9
E10F-STUPR1102-D120	CARBIDE	12	10	6.5	80	25	9	0.5	5	-6	0.4	TP**1102... ⁽¹⁾	1.2
E10H-STUPR1102-D120	CARBIDE	12	10	6.5	100	25	9	0.6	5	-6	0.4	TP**1102... ⁽¹⁾	1.2
E10M-STUPR/L1102-D120	CARBIDE	12	10	6.5	150	25	9	0.6	5	-6	0.4	TP**1102... ⁽¹⁾	1.2
E10M-STUPR/L1103-D120	CARBIDE	12	10	6.5	150	25	9	0.7	5	-10	0.4	TP**1103... ⁽¹⁾	1.4
E12G-STUPR1102-D140	CARBIDE	14	12	7	90	27	11	0.8	5	-4	0.4	TP**1102... ⁽¹⁾	1.2
E12J-STUPR1102-D140	CARBIDE	14	12	7	110	27	11	0.8	5	-4	0.4	TP**1102... ⁽¹⁾	1.2
E12Q-STUPR/L1102-D140	CARBIDE	14	12	7	180	27	11	0.8	5	-4	0.4	TP**1102... ⁽¹⁾	1.2
E12Q-STUPR/L1103-D140	CARBIDE	14	12	7	180	27	11	0.7	5	-6	0.4	TP**1103... ⁽¹⁾	1.4
E12G-STUPR1102-D160	CARBIDE	16	12	9	90	27	11	0.6	5	-3	0.4	TP**1102... ⁽¹⁾	1.2
E12J-STUPR1102-D160	CARBIDE	16	12	9	110	27	11	0.6	5	-3	0.4	TP**1102... ⁽¹⁾	1.2
E12Q-STUPR/L1102-D160	CARBIDE	16	12	9	180	27	11	0.6	5	-3	0.4	TP**1102... ⁽¹⁾	1.2
E16H-STUPR13-D180	CARBIDE	18	16	9	100	32	15	0.9	5	-3	0.4	TP**1303... ⁽¹⁾	1.4
E16R-STUPR/L1103-D180	CARBIDE	18	16	9	200	32	15	0.8	5	-3	0.4	TP**1103... ⁽¹⁾	1.4
E16L-STUPR13-D180	CARBIDE	18	16	9	130	32	15	0.6	5	-3	0.4	TP**1303... ⁽¹⁾	1.4
E16R-STUPR/L13-D180	CARBIDE	18	16	9	200	32	15	0.6	5	-3	0.4	TP**1303... ⁽¹⁾	1.4
E16H-STUPR13-D200	CARBIDE	20	16	11	100	32	15	0.6	5	-3	0.4	TP**1303... ⁽¹⁾	1.4
E16L-STUPR13-D200	CARBIDE	20	16	11	130	32	15	0.6	5	-3	0.4	TP**1303... ⁽¹⁾	1.4
E16R-STUPR13-D200	CARBIDE	20	16	11	200	32	15	0.6	5	-3	0.4	TP**1303... ⁽¹⁾	1.4
E20S-STUPR1103-D220	CARBIDE	22	20	11	250	36	18	0.7	5	-2	0.4	TP**1103... ⁽¹⁾	1.4
E20S-STUPR13-D220	CARBIDE	22	20	11	250	36	18	0.6	5	-2	0.4	TP**1303... ⁽¹⁾	1.4
E25T-STUPR16-D270	CARBIDE	27	25	13.5	300	45	23	0.5	5	-1	0.8	TP**16T3...	3

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (STUPL ** type), and the left hand insert (L) is used for the right hand toolholders (STUPR ** type).

(1) Inserts of TPGH, TPGM and TPGA are not applicable.


SPARE PARTS



Designation	Clamping screw	Wrench
A/E07*-STUPR/L07-...	CSTB-2.2L038	T-7F
A/E08*-STUPR/L07-...	CSTB-2.2L038	T-7F
A/E08*-STUPR/L09-...	CSTB-2.2L038	T-7F
A/E10*-STUPR/L1102-...	CSTB-2.5S	T-8F
A/E10*-STUPR/L1103-...	CSTB-3L050	T-9F
A/E12*-STUPR/L1102-...	CSTB-2.5B	T-8F
A/E12*-STUPR/L1103-...	CSTB-3L050	T-9F
A/E16*-STUPR/L1103-...	CSTB-3S	T-9F
A/E16*-STUPR/L13-...	CSTB-3S	T-9F
A/E20*-STUPR/L1103-...	CSTB-3S	T-9F
A/E20*-STUPR/L13-...	CSTB-3	T-9F
A/E25*-STUPR/L16-...	CSTB-4M	T-15F
A32*-STUPR/L16-...	CSTB-4M	T-15F

A/E-SVQBR/L

Screw-on boring bars, for positive 35° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A12M-SVQBR/L11-D170	STEEL	17	12	10.5	150	24	11	4.5	-5	-10	0.4	VB**1103...	1.2
A16Q-SVQBR/L11-D215	STEEL	21.5	16	13	180	30	15	5	-5	-8	0.4	VB**1103...	1.2
A20R-SVQBR/L11-D255	STEEL	25.5	20	15	200	36	18	5	-5	-6	0.4	VB**1103...	1.2
A25S-SVQBR/L16-D305	STEEL	30.5	25	17.5	250	45	23	5	-5	-8	0.8	VB**1604...	3
E12Q-SVQBR/L11-D170	CARBIDE	17	12	10.5	180	27	11	4.5	-5	-10	0.4	VB**1103...	1.2
E16R-SVQBR/L11-D215	CARBIDE	21.5	16	13	200	32	15	5	-5	-8	0.4	VB**1103...	1.2
E20S-SVQBR/L11-D255	CARBIDE	25.5	20	15	250	36	18	5	-5	-6	0.4	VB**1103...	1.2
E25T-SVQBR/L16-D305	CARBIDE	30.5	25	17.5	300	45	23	5	-5	-8	0.8	VB**1604...	3

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SVQBL type), and the left hand insert (L) is used for the right hand toolholders (SVQBR type).


SPARE PARTS



Designation	Clamping screw	Wrench
A*-SVQBR/L11-D...	CSTB-2.5	T-8F
A25S-SVQBR/L16-D305	CSTB-3.5	T-15F
E*-SVQBR/L11-D...	CSTB-2.5	T-8F
E25T-SVQBR/L16-D305	CSTB-3.5	T-15F

A/E-SVQCR/L

Screw-on boring bars, for positive 35° rhombic inserts



Right hand (R) shown.

Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f ₂	GAMP	GAMF	RE**	Insert	Torque*
A10K-SVQCR/L08-D135	STEEL	13.5	10	8	125	20	9	3	-5	-8	0.4	VC**0802...	0.6
A16Q-SVQCR/L11-D215	STEEL	21.5	16	13	180	30	15	4.9	-5	-8	0.4	VC**1103...	1.2
E10M-SVQCR/L08-D135	CARBIDE	13.5	10	8	150	25	9	3	-5	-8	0.4	VC**0802...	0.6
E16R-SVQCR/L11-D215	CARBIDE	21.5	16	13	200	32	15	4.9	-5	-8	0.4	VC**1103...	1.2

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SVQCL ** type), and the left hand insert (L) is used for the right hand toolholders (SVQCR ** type).

SPARE PARTS

Designation	Clamping screw	Wrench
A10K-SVQCR/L08-D135	CSTB-2L	T-6F
A16Q-SVQCR/L11-D215	CSTB-2.5	T-8F
E10M-SVQCR/L08-D135	CSTB-2L	T-6F
E16R-SVQCR/L11-D215	CSTB-2.5	T-8F

A/E-SVUBR/L

Screw-on boring bars, for positive 35° rhombic inserts



Right hand (R) shown.

Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f ₂	GAMP	GAMF	RE**	Insert	Torque*
A16Q-SVUBR/L11-D200	STEEL	20	16	15.5	180	35	15	8	0	-8	0.4	VB**1103...	1.2
A20R-SVUBR/L11-D250	STEEL	25	20	17.5	200	40	19	8	0	-7	0.4	VB**1103...	1.2
A25S-SVUBR/L16-D320	STEEL	32	25	20.5	250	50	23	8.5	0	-6	0.8	VB**1604...	3
E16R-SVUBR/L11-D245	CARBIDE	24.5	16	16	200	-	15	8	0	-8	0.4	VB**1103...	1.2
E20S-SVUBR/L11-D285	CARBIDE	28.5	20	18	250	-	19	8	0	-7	0.4	VB**1103...	1.2
E25T-SVUBR/L16-D340	CARBIDE	34	25	21	300	-	23	8.5	0	-6	0.8	VB**1604...	3

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SVUBL** type), and the left hand insert (L) is used for the right hand toolholders (SVUBR** type).

SPARE PARTS

Designation	Clamping screw	Wrench
A**-SVUBR/L11-D2*0	CSTB-2.5	T-8F
A25S-SVUBR/L16-D320	CSTB-3.5	T-15F
E**-SVUBR/L11-D2*5	CSTB-2.5	T-8F
E25T-SVUBR/L16-D340	CSTB-3.5	T-15F

A/E-SVUCR/L

Screw-on boring bars, for positive 35° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A12M-SVUCR/L08-D160	STEEL	16	12	11	150	30	11	5.5	0	-8	0.4	VC**0802...	0.6
A25S-SVUCR/L16-D320	STEEL	32	25	19	250	45	23	6.5	0	-5	0.8	VC**1604...	3
E12Q-SVUCR/L08-D180	CARBIDE	18	12	11.5	180	-	11	5.5	0	-8	0.4	VC**0802...	0.6
E25T-SVUCR/L16-D320	CARBIDE	32	25	19	300	-	23	6.5	0	-5	0.8	VC**1604...	3

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SVUCL** type), and the left hand insert (L) is used for the right hand toolholders (SVUCR** type).

SPARE PARTS

Designation	Clamping screw	Wrench
A12M-SVUCR/L08-D160	CSTB-2L	T-6F
A25S-SVUCR/L16-D320	CSTB-3.5	T-15F
E12Q-SVUCR/L08-D180	CSTB-2L	T-6F
E25T-SVUCR/L16-D320	CSTB-3.5	T-15F

A-SVZBR/L

Screw-on boring bars, for positive 35° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	L3	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A16Q-SVZBR/L11-D200	STEEL	20	16	15.5	180	35	12.5	15	8	0	-8	0.4	VB**1103...	1.2
A20R-SVZBR/L11-D250	STEEL	25	20	17.5	200	40	12.5	18	8	0	-7	0.4	VB**1103...	1.2
A25S-SVZBR/L16-D320	STEEL	32	25	24	250	50	17.5	23	12	0	-6	0.8	VB**1604...	3
A32T-SVZBR/L16-D400	STEEL	40	32	27.5	300	72	17.5	30	12	0	-5	0.8	VB**1604...	3

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert (R) is used for the right hand toolholders (SVZBR type), and the left hand insert (L) is used for the left hand toolholders (SVZBL type).

SPARE PARTS

Designation	Clamping screw	Wrench
A**-SVZBR/L11-D2*0	CSTB-2.5	T-8F
A25S-SVZBR/L16-D320	CSTB-3.5	T-15F
A32T-SVZBR/L16-D400	CSTB-3.5L	T-15F

A-SVZCR/L

Screw-on boring bars, for positive 35° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	L3	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A12M-SVZCR/L08-D160	STEEL	16	12	11	150	30	10	11	5.5	0	-8	0.4	VC**0802...	0.6

*Torque: Recommended torque (N-m) for clamping **RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert (R) is used for the right hand toolholders (SVZCR ** type), and the left hand insert (L) is used for the left hand toolholders (SVZCL ** type).

SPARE PARTS

Designation	Clamping screw	Wrench
A12M-SVZCR/L08-D160	CSTB-2L	T-6F

A/E-SWUBR/L

Screw-on boring bars, for positive trigon inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	GAMP	GAMF	RE**	Insert	Torque*
A05F-SWUBR/L03-D060	STEEL	6	5	3	80	9	4.8	0	-13	0.4	WB**0301...	0.6
A06G-SWUBR/L03-D070	STEEL	7	6	3.5	90	11	5.75	0	-12	0.4	WB**0301...	0.6
A07G-SWUBR/L03-D080	STEEL	8	7	4	90	12	6.75	0	-11	0.4	WB**0301...	0.6
A08H-SWUBR03-D060	STEEL	6	8	3.1	100	18	7.5	0	-12	0.4	WB**0301...	0.6
A08H-SWUBR03-D070	STEEL	7	8	3.6	100	20	7.5	0	-12	0.4	WB**0301...	0.6
E05G-SWUBR/L03-D060	CARBIDE	6	5	3	90	10	4.8	0	-13	0.4	WB**0301...	0.6
E06H-SWUBR/L03-D070	CARBIDE	7	6	3.5	100	12	5.75	0	-12	0.4	WB**0301...	0.6
E07H-SWUBR/L03-D080	CARBIDE	8	7	4	100	14	6.75	0	-11	0.4	WB**0301...	0.6
E08K-SWUBR03-D060	CARBIDE	6	8	3.1	125	30	7.5	0	-12	0.4	WB**0301...	0.6
E08K-SWUBR03-D070	CARBIDE	7	8	3.6	125	40	7.5	0	-12	0.4	WB**0301...	0.6

*Torque: Recommended torque (N-m) for clamping **RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SWUBL** type), and the left hand insert (L) is used for the right hand toolholders (SWUBR** type).

SPARE PARTS

Designation	Clamping screw	Wrench
A/E**-SWUBR/L...	CSTB-2	T-6F

A/E-SEZPR/L

Screw-on boring bars, for positive 75° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A04F-SEZPR/L03-D055	STEEL	5.5	4	3.2	80	4	3.8	1.2	0	-8	0.2	EP**03X1...	0.6
A05F-SEZPR/L03-D065	STEEL	6.5	5	3.7	80	5	4.8	1.2	0	-6	0.2	EP**03X1...	0.6
E04G-SEZPR/L03-D055	CARBIDE	5.5	4	3.2	90	5	3.8	1.2	0	-8	0.2	EP**03X1...	0.6
E05G-SEZPR/L03-D065	CARBIDE	6.5	5	3.7	90	6	4.8	1.2	0	-6	0.2	EP**03X1...	0.6

*Torque: Recommended torque (N.m) for clamping **RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert (R) is used for the right hand toolholders (SEZPR ** type), and the left hand insert (L) is used for the left hand toolholders (SEZPL ** type).

SPARE PARTS

Designation	Clamping screw	Wrench
A**-SEZPR/L03-D...	CSTA-1.6	T-6F
E**-SEZPR/L03-D...	CSTA-1.6	T-6F

A-SVJBR/L

Screw-on boring bars, for positive 35° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	GAMP	GAMF	RE**	Insert	Torque*
A20R-SVJBR/L11-D250	STEEL	25	20	2	200	40	18	-5	-5	0.4	VB**1103...	1.2
A25S-SVJBR/L11-D300	STEEL	30	25	3.5	250	50	23	-5	-5	0.4	VB**1103...	1.2

*Torque: Recommended torque (N.m) for clamping **RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SVJBL** type), and the left hand insert (L) is used for the right hand toolholders (SVJBR** type).

SPARE PARTS

Designation	Clamping screw	Wrench
A**-SVJB*11-D...	CSTB-2.5	T-8F

A-SVJCR/L

Screw-on boring bars, for positive 35° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	GAMP	GAMF	RE**	Insert	Torque*
A12M-SVJCR/L08-D160	STEEL	16	12	2	150	28	11	-5	-5	0.4	VC**0802...	0.6
A16Q-SVJCR/L08-D200	STEEL	20	16	2	180	35	15	-5	-5	0.4	VC**0802...	0.6

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SVJCL** type), and the left hand insert (L) is used for the right hand toolholders (SVJCR** type).

SPARE PARTS

Designation	Clamping screw	Wrench
A**-SVJC*08-D...	CSTB-2L	T-6F

A/E-SEXPR/L

Screw-on boring bars, for positive 75° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	GAMP	GAMF	RE**	Insert	Torque*
A04F-SEXPR/L03-D045	STEEL	4.5	4	2.3	80	8	3.8	0	-15	0.2	EP**03X1...	0.6
A04F-SEXPR/L03-D050	STEEL	5	4	2.5	80	8	3.8	0	-13	0.2	EP**03X1...	0.6
A05F-SEXPR/L04-D055	STEEL	5.5	5	2.75	80	9	4.8	0	-12	0.4	EP**0401...	0.6
A06G-SEXPR/L04-D070	STEEL	7	6	3.6	90	11	5.75	0	-12	0.4	EP**0401...	0.6
A08H-SEXPR/L04-D055	STEEL	5.5	8	2.75	100	16	7.5	0	-12	0.4	EP**0401...	0.6
A08H-SEXPR/L04-D070	STEEL	7	8	3.6	100	20	7.5	0	-12	0.4	EP**0401...	0.6
E04G-SEXPR/L03-D045	CARBIDE	4.5	4	2.3	90	9	3.8	0	-15	0.2	EP**03X1...	0.6
E04G-SEXPR/L03-D050	CARBIDE	5	4	2.5	90	9	3.8	0	-13	0.2	EP**03X1...	0.6
E05G-SEXPR/L04-D055	CARBIDE	5.5	5	2.75	90	10	4.8	0	-12	0.4	EP**0401...	0.6
E06H-SEXPR/L04-D070	CARBIDE	7	6	3.6	100	12	5.75	0	-12	0.4	EP**0401...	0.6
E08K-SEXPR/L04-D055	CARBIDE	5.5	8	2.75	125	28	7.5	0	-12	0.4	EP**0401...	0.6
E08K-SEXPR/L04-D070	CARBIDE	7	8	3.6	125	40	7.5	0	-12	0.4	EP**0401...	0.6

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (SEXPL** type), and the left hand insert (L) is used for the right hand toolholders (SEXPR** type).


SPARE PARTS

Designation	Clamping screw	Wrench
A**-SEXPR/L03-D...	CSTA-1.6	T-6F
A**-SEXPR/L04-D...	CSTB-2	T-6F
E**-SEXPR/L03-D...	CSTA-1.6	T-6F
E**-SEXPR/L04-D...	CSTB-2	T-6F

HOW TO USE SVJC(B)R/L-TYPE TOOLS

General machining information



The minimum machinable radius (R) of the internal sphere is 1/2 of the minimum bore diameter (ϕD_m).
The maximum machinable depth of the bore is within the L_2 size of the tool.



Cautionary points

To avoid insert breakage the tool point should not overrun the bore center.

To avoid burr, the depth of cut should be within the corner radius.




Machining examples


Machining of internal sphere

Work material : S45C
Toolholder : A12M-SVJCR08-D160
Insert : VCMT080204-PF (NS730)
Cutting speed : $V_c = \sim 100$ m/min
No of revs. : $n = 3000 \text{ min}^{-1}$ (constant)
Feed : $f = 0.1$ mm/rev
Depth of cut : $a_p = 0.5$ mm


Work material : S45C
Toolholder : A12M-SVJCR08-D160
Insert : VCMT080204-PF (T9015)
Cutting speed : $V_c = \sim 100$ m/min
No of revs. : $n = 3000 \text{ min}^{-1}$ (constant)
Feed : $f = 0.1$ mm/rev
 : $f = 0.05$ mm/rev (only for plunging)
Depth of cut : $a_p = 0.5$ mm




Machining from a solid workpiece



Machining from a pre-drilled bore




Machining from a solid workpiece



Machining from a pre-drilled bore

A/E-SYQBR/L

Screw-on boring bars, for positive 25° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMF	GAMF	RE**	Insert	Torque*
A12M-SYQBR/L11-D170	STEEL	17	12	10.5	150	24	11	4.5	-5	-10	0.4	YW**11T2...	0.6
A16Q-SYQBR/L11-D215	STEEL	21.5	16	13	180	30	15	5	-5	-8	0.4	YW**11T2...	0.6
E12Q-SYQBR/L11-D170	CARBIDE	17	12	10.5	180	27	11	4.5	-5	-10	0.4	YW**11T2...	0.6
E16R-SYQBR/L11-D215	CARBIDE	21.5	16	13	200	32	15	5	-5	-8	0.4	YW**11T2...	0.6

*Torque: Recommended torque (N·m) for clamping


**RE: Standard corner radius

SPARE PARTS

Designation	Clamping screw	Wrench
A**-SYQBR/L11-D...	CSTB-2L	T-6F
E**-SYQBR/L11-D...	CSTB-2L	T-6F

A/E-SYUBR/L

Screw-on boring bars, for positive 25° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMF	GAMF	RE**	Insert	Torque*
A16Q-SYUBR/L11-D200	STEEL	20	16	15.5	180	35	15	8	0	-8	0.4	YW**11T2...	0.6
E12Q-SYUBR/L11-D200	CARBIDE	20	12	13.5	180	27	11	7.5	0	-8	0.4	YW**11T2...	0.6
E16R-SYUBR/L11-D245	CARBIDE	24.5	16	16	200	32	15	8	0	-8	0.4	YW**11T2...	0.6

*Torque: Recommended torque (N·m) for clamping


**RE: Standard corner radius

SPARE PARTS

Designation	Clamping screw	Wrench
A16Q-SYUBR/L11-D200	CSTB-2L	T-6F
E**-SYUBR/L11-D...	CSTB-2L	T-6F

A-PCLNR/L

Lever-lock boring bars, for negative 80° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A16M-PCLNR/L09-D200	STEEL	20	16	11	150	32	15	3	-6	-14	0.8	CN**0903...	1.7
A20Q-PCLNR/L09-D250	STEEL	25	20	13	180	36	18	3	-6	-12	0.8	CN**0903...	1.7
A25R-PCLNR/L09-D320	STEEL	32	25	17	200	45	23	4.5	-6	-11	0.8	CN**0903...	1.7
A25R-PCLNR/L12-D320	STEEL	32	25	17	200	45	23	4.5	-6	-13	0.8	CN**1204...	2.7
A32S-PCLNR/L12-D400	STEEL	40	32	22	250	50	30	6	-6	-11	0.8	CN**1204...	4.8
A40T-PCLNR/L12-D500	STEEL	50	40	27	300	60	37	7	-6	-10	0.8	CN**1204...	4.8
A50U-PCLNR/L12-D630	STEEL	63	50	35	350	65	47	10	-6	-8	0.8	CN**1204...	4.8

*Torque: Recommended torque (N·m) for clamping **RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (PCLNL ** type), and the left hand insert (L) is used for the right hand toolholders (PCLNR ** type).

SPARE PARTS

Designation	Shim	Clamping screw 1	Clamping screw 2	Wrench 1	Wrench 2	Spring	Lever	Oil supply attachment (Optional parts)	Screw for oil hole (Optional parts)
A**-PCLNR/L09-D**0	-	LCS22A	-	P-2F	-	-	LCL32N	EA-25	SSHM5-6
A25R-PCLNR/L12-D320	-	LCS43	-	-	P-2.5	-	LCL43N	EA-25	SSHM5-6
A32S-PCLNR12-D400	LSC42BR	-	LCS4	-	P-3	LSP4	LCL4	EA-32	SSHM5-6
A32S-PCLNL12-D400	LSC42BL	-	LCS4	-	P-3	LSP4	LCL4	-	SSHM6-6
A40T-PCLNR12-D500	LSC42BR	-	LCS4	-	P-3	LSP4	LCL4	-	SSHM6-6
A40T-PCLNL12-D500	LSC42BL	-	LCS4	-	P-3	LSP4	LCL4	-	SSHM6-6
A50U-PCLNR12-D630	LSC42BR	-	LCS4	-	P-3	LSP4	LCL4	-	SSHM6-6
A50U-PCLNL12-D630	LSC42BL	-	LCS4	-	P-3	LSP4	LCL4	-	SSHM6-6

A-PDUNR/L

Lever-lock boring bars, for negative 55° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A20Q-PDUNR/L11-D250	STEEL	25	20	13	180	36	18	3	-6	-14	0.8	DN**1104...	1.7
A25R-PDUNR/L11-D320	STEEL	32	25	17	200	45	23	4.5	-6	-12	0.8	DN**1104...	2.7
A32S-PDUNR/L15-D400	STEEL	40	32	22	250	50	30	6	-6	-13	0.8	DN**1504...	4.8
A40T-PDUNR/L15-D500	STEEL	50	40	27	300	60	37	7	-6	-10	0.8	DN**1504...	4.8
A50U-PDUNR/L15-D630	STEEL	63	50	35	350	65	47	10	-6	-8	0.8	DN**1504...	4.8
A32S-PDUNR/L1506-D400	STEEL	40	32	22	250	50	30	6	-6	-13	0.8	DN**1506...	4.8
A40T-PDUNR/L1506-D500	STEEL	50	40	27	300	60	37	7	-6	-11	0.8	DN**1506...	4.8
A50U-PDUNR/L1506-D630	STEEL	63	50	35	350	65	47	10	-6	-10	0.8	DN**1506...	4.8

*Torque: Recommended torque (N·m) for clamping


**RE: Standard corner radius

SPARE PARTS

Designation	Shim	Clamping screw 1	Clamping screw 2	Wrench 1	Wrench 2	Spring	Lever	Oil supply attachment (Optional parts)	Screw for oil hole (Optional parts)
A20Q-PDUNR/L11-D250	-	LCS22A	-	P-2F	-	-	LCL33NL	EA-20	SSHM2.5-3
A25R-PDUNR/L11-D320	ELSD317BR/L	-	LCS3	-	P-2.5	LSP3	LCL33L	EA-25	SSHM3-4
A32S-PDUNR/L15-D400	LSD42BR/L	-	LCS4	-	P-3	LSP4	LCL4	EA-32	SSHM5-6
A40T-PDUNR/L15-D500	LSD42BR/L	-	LCS4	-	P-3	LSP4	LCL4	-	SSHM6-6
A50U-PDUNR/L15-D630	LSD42BR/L	-	LCS4	-	P-3	LSP4	LCL4	-	SSHM6-6
A32S-PDUNR/L1506-D400	ELSD42	-	ELCS4	-	P-3	LSP4S	LCL44	EA-20	SSHM5-6
A40T-PDUNR/L1506-D500	ELSD42	-	ELCS4	-	P-3	LSP4S	LCL44	-	SSHM6-6
A50U-PDUNR/L1506-D630	ELSD42	-	ELCS4	-	P-3	LSP4S	LCL44	-	SSHM6-6

A-PDZNR/L

Lever-lock boring bars, for negative 55° rhombic inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A32S-PDZNR/L15-D400	STEEL	40	32	22	250	50	30	11.5	-6	-13	0.8	DN**1504...	4.8
A40T-PDZNR/L15-D500	STEEL	50	40	27	300	60	37	14.5	-6	-10	0.8	DN**1504...	4.8
A50U-PDZNR/L15-D630	STEEL	63	50	35	350	65	47	14.5	-6	-8	0.8	DN**1504...	4.8

*Torque: Recommended torque (N-m) for clamping **RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert (R) is used for the right hand toolholders (PDZNR** type), and the left hand insert (L) is used for the left hand toolholders (PDZNL** type).

SPARE PARTS

Designation	Shim	Clamping screw	Wrench	Spring	Lever	Oil supply attachment (Optional parts)	Screw for oil hole (Optional parts)
A32S-PDZNR15-D400	LSZ42BR	LCS4	P-3	LSP4	LCL4	EA-32	SSHM4-5
A32S-PDZNL15-D400	LSZ42BL	LCS4	P-3	LSP4	LCL4	EA-32	SSHM4-5
A40T-PDZNR15-D500	LSZ42BR	LCS4	P-3	LSP4	LCL4	-	SSHM5-6
A40T-PDZNL15-D500	LSZ42BL	LCS4	P-3	LSP4	LCL4	-	SSHM5-6
A50U-PDZNR15-D630	LSZ42BR	LCS4	P-3	LSP4	LCL4	-	SSHM6-6
A50U-PDZNL15-D630	LSZ42BL	LCS4	P-3	LSP4	LCL4	-	SSHM6-6

S-PSKNR

Lever-lock boring bars, for negative square inserts



Designation	Material	DMIN	DCONMS	WF	LF	LH	H	B	GAMF	RE**	Insert
S32S-PSKNR12	STEEL	40	32	22	250	50	30	29.5	-10	0.8	SN**1204...
S40T-PSKNR12	STEEL	50	40	27	300	55	37	37.5	-10	0.8	SN**1204...
S50U-PSKNR12	STEEL	63	50	35	350	65	47	47.5	-8	0.8	SN**1204...

**RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert is used for left hand toolholders and the left hand insert is used for right hand toolholders.

SPARE PARTS

Designation	Shim	Clamping screw	Wrench	Spring	Lever
S**-PSKNR12	LSS42BR	LCS4	P-3	LSP4	LCL4

A-PTFNR/L

Lever lock type boring bar, for negative triangle inserts



Cutting edge style F

Right hand (R) shown.

Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A25R-PTFNR/L16-D320	STEEL	32	25	17	200	45	23	1.2	-6	-12	0.8	TN**1604...	2.7
A32S-PTFNR/L16-D400	STEEL	40	32	22	250	50	30	1.1	-6	-10	0.8	TN**1604...	2.7
A40T-PTFNR/L16-D500	STEEL	50	40	27	300	60	37	1.1	-6	-10	0.8	TN**1604...	2.7
A50U-PTFNR/L16-D630	STEEL	63	50	35	350	65	47	1.1	-6	-8	0.8	TN**1604...	2.7

*Torque: Recommended torque (N-m) for clamping **RE: Standard corner radius


Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (PTFNL ** type), and the left hand insert (L) is used for the right hand toolholders (PTFNR ** type).

SPARE PARTS

Designation	Shim	Clamping screw	Wrench	Spring	Lever	Oil supply attachment (Optional parts)	Screw for oil hole (Optional parts)
A25R-PTFNR/L16-D320	ELST317BR/L	LCS3	P-2.5	LSP3	LCL33	(EA-25)	(SSHM4-5)
A32S-PTFNR/L16-D400	LST317BR/L	LCS3	P-2.5	LSP3	LCL3	(EA-32)	(SSHM4-5)
A40T-PTFNR/L16-D500	LST317BR/L	LCS3	P-2.5	LSP3	LCL3	-	(SSHM6-6)
A50U-PTFNR/L16-D630	LST317BR/L	LCS3	P-2.5	LSP3	LCL3	-	(SSHM6-6)

A-PTUNR/L

Lever-lock boring bars, for negative triangle inserts



Cutting edge style U

Right hand (R) shown.

Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A16M-PTUNR/L11-D200	STEEL	20	16	11	150	32	15	1	-6	-14	0.4	TN**1103...	1.7
A20Q-PTUNR/L11-D250	STEEL	25	20	13	180	36	18	1	-6	-12	0.4	TN**1103...	1.7
A25R-PTUNR/L16-D320	STEEL	32	25	17	200	45	23	1.4	-6	-12	0.8	TN**1604...	2.7
A32S-PTUNR/L16-D400	STEEL	40	32	22	250	50	30	1.3	-6	-10	0.8	TN**1604...	2.7

*Torque: Recommended torque (N-m) for clamping **RE: Standard corner radius

Note: The insert hole conforms to the ISO standard.

Tool holder length may be different to the ISO standard.


When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (PTUNL ** type), and the left hand insert (L) is used for the right hand toolholders (PTUNR ** type).

SPARE PARTS

Designation	Shim	Clamping screw 1	Clamping screw 2	Wrench 1	Wrench 2	Spring	Lever	Oil supply attachment (Optional parts)	Screw for oil hole (Optional parts)
A16M-PTUNR/L11-D200	-	LCS22A	-	P-2F	-	-	LCL22N	-	(SSHM3-4)
A20Q-PTUNR/L11-D250	-	LCS22A	-	P-2F	-	-	LCL22N	(EA-20)	(SSHM3-4)
A25R-PTUNR/L16-D320	ELST317BR/L	-	LCS3	-	P-2.5	LSP3	LCL33	(EA-25)	(SSHM4-5)
A32S-PTUNR/L16-D400	LST317BR/L	-	LCS3	-	P-2.5	LSP3	LCL3	(EA-32)	(SSHM4-5)

A-PVUNR/L

Lever-lock boring bars, for negative 35° rhombic inserts




Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMP	GAMF	RE**	Insert	Torque*
A25R-PVUNR/L16-D370	STEEL	37	25	22	200	45	23	9.5	-5	-14	0.8	V/YN**1604...	2.7
A32S-PVUNR/L16-D400	STEEL	40	32	22	250	50	30	6	-5	-12	0.8	V/YN**1604...	2.7
A40T-PVUNR/L16-D500	STEEL	50	40	27	300	60	37	7	-5	-10	0.8	V/YN**1604...	2.7

*Torque: Recommended torque (N-m) for clamping

**RE: Standard corner radius

SPARE PARTS

Designation	Shim	Clamping screw	Wrench	Spring	Lever	Oil supply attachment (Optional parts)	Screw for oil hole (Optional parts)
A25R-PVUNR/L16-D370	LSV317BR/L	LCS3V	P-2.5	LSP3	LCL3V	EA-25	SSHM4-5
A32S-PVUNR/L16-D400	LSV317BR/L	LCS3V	P-2.5	LSP3	LCL3V	EA-32	SSHM4-5
A40T-PVUNR/L16-D500	LSV317BR/L	LCS3V	P-2.5	LSP3	LCL3V	-	SSHM5-6

A-PWLNRL**Lever-lock boring bars, for negative trigon inserts**

Designation	Material	DMIN	DCONMS	WF	LF	LH	H	f2	GAMF	GAMF	RE**	Insert	Torque*
A16M-PWLNRL06-D200	STEEL	20	16	11	150	32	15	3	-8	-17	0.8	WN**0604...	1.7
A20Q-PWLNRL06-D250	STEEL	25	20	13	180	36	18	3	-6	-14	0.8	WN**0604...	1.7
A25R-PWLNRL06-D320	STEEL	32	25	17	200	45	23	4.5	-6	-12	0.8	WN**0604...	2.7
A32S-PWLNRL06-D400	STEEL	40	32	22	250	50	30	6	-6	-11	0.8	WN**0604...	2.7
A25R-PWLNRL08-D320	STEEL	32	25	17	200	45	23	4.5	-6	-13	0.8	WN**0804...	2.7
A32S-PWLNRL08-D400	STEEL	40	32	22	250	50	30	6	-6	-11	0.8	WN**0804...	4.8
A40T-PWLNRL08-D500	STEEL	50	40	27	300	60	37	7	-6	-10	0.8	WN**0804...	4.8

*Torque: Recommended torque (N-m) for clamping **RE: Standard corner radius

Note: When using a right or left hand insert, the right hand insert (R) is used for the left hand toolholders (PWLNRL ** type), and the left hand insert (L) is used for the right hand toolholders (PCLNR ** type).

SPARE PARTS

Designation	Shim	Clamping screw 1	Clamping screw 2	Wrench 1	Wrench 2	Spring	Lever	Oil supply attachment (Optional parts)	Screw for oil hole (Optional parts)
A16M-PWLNRL06-D200	-	LCS33	-	P-2F	-	-	LCL33N	-	SSHM3-4
A20Q-PWLNRL06-D250	-	LCS33	-	P-2F	-	-	LCL33N	EA-20	SSHM3-4
A25R-PWLNRL06-D320	LSW312BR/L	-	LCS3B	-	P-2.5	LSP3	LCL3	EA-25	SSHM4-5
A32S-PWLNRL06-D400	LSW312BR/L	-	LCS3	-	P-2.5	LSP3	LCL3	EA-32	SSHM4-5
A25R-PWLNRL08-D320	-	LCS43	-	-	P-2.5	-	LCL43N	EA-25	SSHM4-5
A32S-PWLNRL08-D400	LSW42BR/L	-	LCS4	-	P-3	LSP4	LCL4	EA-32	SSHM4-5
A40T-PWLNRL08-D500	LSW42BR/L	-	LCS4	-	P-3	LSP4	LCL4	-	SSHM4-5

Positive type



**Rhombic, 80°
with hole
Positive 7°**

[illegible][illegible]

● : Line up

TurnLine - Insert

● : Continuous cutting
 ● : Light interrupted cutting
 ✱ : Heavy interrupted cutting

Positive type



**Rhombic, 80°
with hole
Positive 7°**

P	Steel
M	Stainless
K	Cast iron
N	Non-ferrous
S	Superalloys
H	Hard materials

Application	Chipbreaker	Designation	Corner radius	Coated										Coated cermet		Cermet	
				T9215	T9115	T9125	T6120	T6130	AH630	AH645	AH120	AH725	AH8005	AH8015	GH730	GT9530	NS9530
Finishing to light cutting		PSS CCMT060204-PSS	0.4	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT060208-PSS	0.8	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT09T304-PSS	0.4	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT09T308-PSS	0.8	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT120404-PSS	0.4	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT120408-PSS	0.8	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT120412-PSS	1.2	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Finishing to medium cutting		PS CCMT060202-PS	0.2	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT060204-PS	0.4	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT060208-PS	0.8	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT09T302-PS	0.2	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT09T304-PS	0.4	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT09T308-PS	0.8	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT120404-PS	0.4	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT120408-PS	0.8	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		CCMT120412-PS	1.2	●	●	●	●	●	●	●	●	●	●	●	●	●	●

● : Line up

Positive type



**Rhombic, 80°
with hole
Positive 7°**

[illegible]

● : Line up

TurnLine - Insert




● : Continuous cutting
 ● : Light interrupted cutting
 ✱ : Heavy interrupted cutting

Positive type



**Rhombic, 80°
with hole
Positive 7°**

P	Steel
M	Stainless
K	Cast iron
N	Non-ferrous
S	Superalloys
H	Hard materials

Application	Chipbreaker	Designation	Corner radius	Coated												Coated cermet		Cermet		Uncoated		
				T9215	T9115	T9125	T6120	T6130	AH630	AH645	T515	T5115	AH120	AH725	GH110	GH330	GH730	GT9530		NS9530		TH10
Finishing		W15 CCGT060200R-W15	0.03																		●	
		CCGT060200L-W15	0.03																●		●	
		CCGT060202R-W15	0.2																●		●	
		CCGT060202L-W15	0.2													●			●		●	
		CCGT060204R-W15	0.4												●				●		●	
		CCGT060204L-W15	0.4											●	●		●		●		●	●
		W20 CCGT09T302R-W20	0.2																●		●	
		CCGT09T302L-W20	0.2														●		●		●	
		CCGT09T304R-W20	0.4																●			
		CCGT09T304L-W20	0.4											●	●		●		●		●	
		CCGT09T308R-W20	0.8																●			
		CCGT09T308L-W20	0.8														●		●			
Medium cutting		PM CCMT060204-PM	0.4	●	●	●	●	●	●			●	●			●		●				
		CCMT060208-PM	0.8	●	●	●	●	●	●			●	●			●		●				
		CCMT09T304-PM	0.4	●	●	●	●	●	●			●	●			●		●				
		CCMT09T308-PM	0.8	●	●	●	●	●	●			●	●			●		●				
		CCMT09T312-PM	1.2	●	●	●	●	●	●				●									
		CCMT120408-PM	0.8				●	●	●	●			●									
		CCMT120412-PM	1.2				●	●	●	●			●									
Finishing to medium cutting		CM CCMT060204-CM	0.4							●	●											
		CCMT060208-CM	0.8								●	●										
		CCMT09T304-CM	0.4								●	●										
		CCMT09T308-CM	0.8								●	●										
		CCMT09T312-CM	1.2									●										
		CCMT120404-CM	0.4									●										
		CCMT120408-CM	0.8									●										

● : Line up

TurnLine - Insert

- : Continuous cutting
- ◐ : Light interrupted cutting
- ⊕ : Heavy interrupted cutting

Positive type




**Rhombic, 80°
with hole
Positive 7°**

	P	M	K	N	S	H
Steel	● ● ● ● ●					
Stainless	● ● ● ● ●					
Cast iron	●					
Non-ferrous						
Superalloys	●	● ●				
Hard materials						

[illegible]

Positive type

[illegible]


● : Line up

100

- : Continuous cutting
- ◐ : Light interrupted cutting
- ⊗ : Heavy interrupted cutting

Positive type

 Rhombic, 80°
with hole
Positive 11°

[illegible][illegible]

● : Line up

Positive type



**Rhombic, 55°
with hole
Positive 7°**

[illegible][illegible]

46

- : Continuous cutting
- ◐ : Light interrupted cutting
- ⊗ : Heavy interrupted cutting



**Rhombic, 55°
with hole
Positive 7°**

[illegible][illegible]

● : Line up

Positive type



**Rhombic, 55°
with hole
Positive 7°**

[illegible]

● : Line up

100

- : Continuous cutting
- ◐ : Light interrupted cutting
- ⊗ : Heavy interrupted cutting



Rhombic, 55°
with hole
Positive 7°

[illegible][illegible]

● : Line up

- : Continuous cutting
- ◐ : Light interrupted cutting
- ⊕ : Heavy interrupted cutting

New



**Rhombic, 55°
with hole
Positive 11°**

[illegible]

● : Line up

- : Continuous cutting
- ◐ : Light interrupted cutting
- ⊕ : Heavy interrupted cutting

**Rhombic, 75°
with hole
Positive 11°**

[illegible][illegible]

● : Line up

Positive type



**Rhombic, 75°
with hole
Positive 11°**

[illegible][illegible]

52

TurnLine - Insert

● : Continuous cutting
 ● : Light interrupted cutting
 ✖ : Heavy interrupted cutting

Positive type



Round,
with hole
Positive 7°

P	Steel
M	Stainless
K	Cast iron
N	Non-ferrous
S	Superalloys
H	Hard materials

Application	Chipbreaker	Designation	Corner radius	Coated															
				T5115															
Finishing to medium cutting		CM	RCMT0502M0-CM	-	●														
			RCMT0602M0-CM	-	●														
			RCMT0803M0-CM	-	●														

POSITIVE TYPE



Square, 90°
with hole
Positive 7°

P	Steel
M	Stainless
K	Cast iron
N	Non-ferrous
S	Superalloys
H	Hard materials

Application	Chipbreaker	Designation	Corner radius	Coated										Coated cermet		Cermet		
				T9215	T9115	T9125	T6120	T6130	AH630	AH645	T515	T5115	AH725	GT9530		NS9530		
Finishing to medium cutting		PS	SCMT09T304-PS	0.4	●	●	●	●	●	●			●	●		●		
			SCMT09T308-PS	0.8	●	●	●	●	●	●			●	●		●		
			SCMT120404-PS	0.4	●	●	●	●	●	●			●	●		●		
			SCMT120408-PS	0.8	●	●	●	●	●	●			●	●		●		
Medium cutting		PM	SCMT09T304-PM	0.4	●	●	●	●	●	●			●			●		
			SCMT09T308-PM	0.8	●	●	●	●	●	●			●			●		
			SCMT120408-PM	0.8	●	●	●	●	●	●			●			●		
			SCMT120412-PM	1.2			●	●	●	●			●			●		
Finishing to medium cutting		CM	SCMT09T304-CM	0.4							●	●						
			SCMT09T308-CM	0.8							●	●						
			SCMT09T312-CM	1.2								●						
			SCMT120404-CM	0.4							●	●						
			SCMT120408-CM	0.8							●	●						

● : Line up

TurnLine - Insert

● : Continuous cutting
 ● : Light interrupted cutting
 ✱ : Heavy interrupted cutting

Positive type



Square, 90°
 with hole
 Positive 11°

P	Steel
M	Stainless
K	Cast iron
N	Non-ferrous
S	Superalloys
H	Hard materials

Application	Chipbreaker	Designation	Corner radius	Coated										Coated cermet		Cermet		Uncoated	
				T9215	T9115	T9125	T6120	T6130	T515	T5115	AH630	AH645	AH725	GT9530		NS9530		TH10	
Finishing to medium cutting		PS SPMT090304-PS	0.4	●	●	●	●	●			●	●	●	●		●			
		SPMT090308-PS	0.8	●	●	●	●	●			●	●	●	●		●			
		SPMT120404-PS	0.4	●	●	●	●	●			●	●	●						
		SPMT120408-PS	0.8	●	●	●	●	●			●	●	●						
Finishing		W15 SPGT090302L-W15	0.2													●			
		SPGT090304L-W15	0.4													●		●	
		SPGT090308R-W15	0.8															●	
		SPGT090308L-W15	0.8													●		●	
		W20 SPGT120404L-W20	0.4													●			
Finishing to medium cutting		CM SPMT090304-CM	0.4							●									
		SPMT090308-CM	0.8							●									
		SPMT120404-CM	0.4						●	●									
		SPMT120408-CM	0.8						●	●									

● : Line up

TurnLine - Insert

● : Continuous cutting
 ● : Light interrupted cutting
 ✱ : Heavy interrupted cutting

Positive type



Triangular, 60°
with hole
Positive 7°

P	Steel
M	Stainless
K	Cast iron
N	Non-ferrous
S	Superalloys
H	Hard materials

Application	Chipbreaker	Designation	Corner radius	Coated					Coated cermet		Cermet		Uncoated	
				T9215	T9115	T9125	AH725	SH725	J740	GT9530	NS9530	NS520	TH10	
Precision finishing		01 TCGT090204-01	0.4	●	●	●	✱	●	●	●	●	●	●	
		TCGT110202-01	0.2					●				●	●	
		TCGT110204-01	0.4							●		●	●	
		TCGT110208-01	0.8								●		●	
		TCGT16T304-01	0.4										●	
		TCGT16T308-01	0.8									●	●	
Precision finishing (Sharp edge)		01 TCGT110202F-01	0.2					●						
Finishing		PSF TCMT090202-PSF	0.2				●							
		TCMT090204-PSF	0.4	●	●	●	●							
		TCMT110202-PSF	0.2				●							
		TCMT110204-PSF	0.4	●	●	●	●							
		TCMT110302-PSF	0.2				●							
		TCMT110304-PSF	0.4	●	●	●	●							
		TCMT16T304-PSF	0.4	●	●	●	●							
Finishing to light cutting		PSS TCMT090204-PSS	0.4	●	●	●	●							
		TCMT090208-PSS	0.8	●	●	●	●							
		TCMT110204-PSS	0.4	●	●	●	●							
		TCMT110208-PSS	0.8	●	●	●	●							
		TCMT110304-PSS	0.4	●	●	●	●							
		TCMT110308-PSS	0.8	●	●	●	●							
		TCMT16T304-PSS	0.4	●	●	●	●							
		TCMT16T308-PSS	0.8	●	●	●	●							
		TCMT16T312-PSS	1.2	●	●	●	●							

● : Line up

TurnLine - Insert

- : Continuous cutting
- ◐ : Light interrupted cutting
- ⊗ : Heavy interrupted cutting

Positive type



**Triangular, 60°
with hole
Positive 7°**

[illegible][illegible]

● : Line up

Positive type



**Triangular, 60°
with hole
Positive 7°**

[illegible][illegible]

58

- : Continuous cutting
- ◐ : Light interrupted cutting
- ⊗ : Heavy interrupted cutting



**Triangular, 60°
with hole
Positive 7°**

[illegible][illegible]

● : Line up

Positive type



**Triangular, 60°
with hole
Positive 11°**

[illegible]

● : Line up

TurnLine - Insert

● : Continuous cutting
 ● : Light interrupted cutting
 ✱ : Heavy interrupted cutting

Positive type



Triangular, 60°
with hole
Positive 11°

P	Steel
M	Stainless
K	Cast iron
N	Non-ferrous
S	Superalloys
H	Hard materials

Application	Chipbreaker	Designation	Corner radius	Coated										Coated cermet		Cermet			
				T9215	T9115	T9125	T6120	T6130	AH630	AH645	AH120	AH725	GH730	GT9530		NS9530			
Finishing to light cutting		PSS TPMT090204-PSS	0.4	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT090208-PSS	0.8	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT110204-PSS	0.4	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT110208-PSS	0.8	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT110304-PSS	0.4	●	●	●	●	●	●	●	●	●	●	●					
		TPMT110308-PSS	0.8	●	●	●	●	●	●	●	●	●	●	●					
		TPMT130304-PSS	0.4	●	●	●	●	●	●	●	●	●	●	●					
		TPMT130308-PSS	0.8	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT16T304-PSS	0.4	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT16T308-PSS	0.8	●	●	●	●	●	●	●	●	●	●	●		●			
Finishing to medium cutting		PS TPMT090202-PS	0.2	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT090204-PS	0.4	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT090208-PS	0.8	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT110202-PS	0.2	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT110204-PS	0.4	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT110208-PS	0.8	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT110304-PS	0.4	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT110308-PS	0.8	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT130302-PS	0.2	●	●	●					●			●		●			
		TPMT130304-PS	0.4	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT130308-PS	0.8	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT16T304-PS	0.4	●	●	●	●	●	●	●	●	●	●	●		●			
		TPMT16T308-PS	0.8	●	●	●	●	●	●	●	●	●	●	●		●			

● : Line up

- : Continuous cutting
- ◐ : Light interrupted cutting
- ⊕ : Heavy interrupted cutting

**Triangular, 60°
with hole
Positive 11°**

[illegible][illegible]

● : Line up

Positive type



**Triangular, 60°
with hole
Positive 11°**

[illegible]

● : Line up

- : Continuous cutting
- ◐ : Light interrupted cutting
- ⊕ : Heavy interrupted cutting



**Triangular, 60°
with hole
Positive 11°**

[illegible][illegible]

● : Line up

- : Continuous cutting
- ◐ : Light interrupted cutting
- ⊗ : Heavy interrupted cutting

**Rhombic, 35°
with hole
Positive 5°**

[illegible]

● : Line up

100

- : Continuous cutting
- ◐ : Light interrupted cutting
- ⊗ : Heavy interrupted cutting

Positive


[illegible][illegible]

● : Line up

TurnLine - Insert

● : Continuous cutting
● : Light interrupted cutting
✱ : Heavy interrupted cutting

Positive type



Rhombic, 35°
with hole
Positive 7°

P	Steel
M	Stainless
K	Cast iron
N	Non-ferrous
S	Superalloys
H	Hard materials

Application	Chipbreaker	Designation	Corner radius	Coated												Coated cermet		Cermet		
				T9215	T9115	T9125	T6120	T6130	T515	T5115	AH630	AH645	AH120	AH725	AH8005	AH8015	AH905	GT9530		
Finishing	PSF	VCMT080202-PSF	0.2																	
		VCMT080204-PSF	0.4	●	●	●						●					●			
		VCMT110302-PSF	0.2									●								
		VCMT110304-PSF	0.4	●	●	●						●								
		VCMT160404-PSF	0.4	●	●	●						●	●	●	●	●	●	●	●	●
		VCMT160408-PSF	0.8	●	●	●						●	●	●	●	●	●	●	●	●
	PF	VCMT080202-PF	0.2														●		●	
		VCMT080204-PF	0.4														●		●	
		VCMT160404-PF	0.4														●		●	
		VCMT160408-PF	0.8														●		●	
Finishing to light cutting		PSS VCMT110304-PSS	0.4	●	●	●	●	●			●	●		●		●		●		
		VCMT110308-PSS	0.8	●	●	●	●	●			●	●		●		●		●		
		VCMT160404-PSS	0.4	●	●	●	●	●			●	●		●	●	●	●	●	●	
		VCMT160408-PSS	0.8	●	●	●	●	●			●	●		●	●	●	●	●	●	
	Finishing to medium cutting		PS VCMT110302-PS	0.2	●	●	●	●	●			●	●		●	●	●		●	
VCMT110304-PS			0.4	●	●	●	●	●			●	●		●	●	●		●		
VCMT110308-PS			0.8	●	●	●	●	●			●	●		●	●	●		●		
VCMT160404-PS			0.4	●	●	●	●	●			●	●	●	●	●	●	●	●	●	
VCMT160408-PS			0.8	●	●	●	●	●			●	●	●	●	●	●	●	●	●	
		CM VCMT080204-CM	0.4						●											
		VCMT160404-CM	0.4						●	●										
		VCMT160408-CM	0.8						●	●										
		VCMT160412-CM	1.2							●										

● : Line up

- : Continuous cutting
- ◐ : Light interrupted cutting
- ⊗ : Heavy interrupted cutting

Positive type

 **Trigon, 80°**
with hole
Positive 5°

[illegible][illegible]

● : Line up

STANDARD CUTTING CONDITIONS

ISO	Operation	Work condition	Chip-breaker	Grade	Depth of cut ap (mm)	Feed f (mm/rev)	Cutting speed: Vc (m/min)		
							Low carbon steels, Alloy steels	Medium carbon steels, Alloy steels	High carbon steels, Alloy steels
P	Precision finishing	Continuous	01	NS9530	0.05 - 0.5	0.03 - 0.15	150 - 250	80 - 220	80 - 180
		Light interrupted	01	NS9530	0.05 - 0.5	0.03 - 0.15	150 - 250	80 - 220	80 - 180
	Finishing	Continuous	PSS	NS9530	0.1 - 0.5	0.05 - 0.3	150 - 250	80 - 220	80 - 180
		Light interrupted	PSS	NS9530	0.1 - 0.5	0.05 - 0.3	150 - 250	80 - 220	80 - 180
		Heavy interrupted	PSS	NS9530	0.1 - 0.5	0.05 - 0.3	150 - 250	80 - 220	80 - 180
	Finishing to light cutting	Continuous	PS	NS9530	0.3 - 2.0	0.08 - 0.3	150 - 250	80 - 220	80 - 180
		Light interrupted	PS	NS9530	0.3 - 2.0	0.08 - 0.3	150 - 250	80 - 220	80 - 180
		Heavy interrupted	PS	NS9530	0.3 - 2.0	0.08 - 0.3	150 - 250	80 - 220	80 - 180
	Finishing to medium cutting	Continuous to Heavy interrupted	PS	T9215	0.5 - 2.5	0.08 - 0.3	120 - 300	100 - 300	80 - 250
		Heavy interrupted	PS	T9125	0.5 - 2.5	0.08 - 0.3	120 - 250	80 - 180	80 - 120
	Medium cutting	Continuous to Heavy interrupted	PM	T9215	1.0 - 3.0	0.15 - 0.3	120 - 300	100 - 300	80 - 250
		Heavy interrupted	PM	T9125	1.0 - 3.0	0.15 - 0.3	120 - 250	80 - 180	80 - 120

Low carbon steels, Alloy steels: S10C, SCM415, SS400, SCr420H, etc. C10, 18CrMo4, E275A, 20Cr4, etc. Medium carbon steels, Alloy steels: S45C, SCM440, etc. C45, 42CrMo4, etc. Hi carbon steels, Alloy steels: SNCM439, etc. 41CrNiMo2, etc.

ISO	Operation	Work condition	Chip-breaker	Grade	Depth of cut ap (mm)	Feed f (mm/rev)	Cutting speed Vc (m/min)
M	Precision finishing	Continuous	Whh	GH330	0.05 - 2.0	0.03 - 0.2	100 - 150
		Continuous	PSF	AH725	0.1 - 0.5	0.05 - 0.3	50 - 150
	Finishing	Light interrupted	PSF	AH725	0.1 - 0.5	0.05 - 0.3	50 - 150
		Heavy interrupted	PSF	AH725	0.1 - 0.5	0.05 - 0.3	50 - 120
		Continuous	PSS	AH630	0.3 - 2.0	0.08 - 0.3	90 - 190
	Finishing to light cutting	Light interrupted	PSS	AH630	0.3 - 2.0	0.08 - 0.3	90 - 190
		Heavy interrupted	PSS	AH630	0.3 - 2.0	0.08 - 0.3	90 - 190
	Finishing to medium cutting	Continuous	PS	T6130	0.5 - 2.5	0.08 - 0.3	100 - 200
		Light interrupted	PS	AH630	0.5 - 2.5	0.08 - 0.3	90 - 190
		Heavy interrupted	PS	AH630	0.5 - 2.5	0.08 - 0.3	90 - 190
	Medium cutting	Continuous	PM	T6130	1.0 - 3.0*	0.15 - 0.3	100 - 200
		Light interrupted	PM	AH630	1.0 - 3.0*	0.15 - 0.3	90 - 190
		Heavy interrupted	PM	AH630	1.0 - 3.0*	0.15 - 0.3	90 - 190

* For CCMT0602 and DCMT0702 type inserts, ap = 0.5 - 2.5

Stainless steels: SUS304, SUS316, etc. X5CrNi18-9, X5CrNiMo17-12-3, etc.

ISO	Operation	Work condition	Chip-breaker	Grade	Depth of cut ap (mm)	Feed f (mm/rev)	Cutting speed: Vc (m/min)	
							Grey cast irons	Ductile cast irons
K	Finishing	Continuous	CM	T515	0.05 - 2.0	0.05 - 0.3	150 - 700	150 - 300
		Heavy interrupted	CM	T515	0.05 - 2.0	0.05 - 0.3	100 - 200	100 - 200
	Medium cutting	Light interrupted	CM	T515	0.05 - 2.0	0.05 - 0.3	100 - 300	100 - 250

Grey cast irons: FC250, etc. 250, etc.

Ductile cast irons: FCD450, etc. 450-10S, etc.


ISO	Operation	Work condition	Chip-breaker	Grade	Depth of cut ap (mm)	Feed f (mm/rev)	Cutting speed: Vc (m/min)	
							Titanium alloys	Ni-base alloys
S	Finishing	Continuous	PSS	AH8015	0.3 - 2.0	0.02 - 0.3	20 - 150	20 - 100
		Light interrupted	PSS	AH8015	0.3 - 2.0	0.02 - 0.3	20 - 150	20 - 100
	Finishing to medium cutting	Continuous	PS	AH8015	0.5 - 2.5	0.02 - 0.3	20 - 150	20 - 100
		Light interrupted	PS	AH8015	0.5 - 2.5	0.02 - 0.3	20 - 150	20 - 100

Ni-base alloys: INCONEL718 etc.

Titanium alloys: Ti - 6Al - 4V etc.

BLM sleeves

Standard Sleeves for SJB-Mini series with round shank



Designation	DCONMS	DCONWS	BD	LF	H	S1	S2	S3
BLM159-04	15.875	4	15	100	15	5	15	15
BLM159-05	15.875	5	15	100	15	5	15	15
BLM159-06	15.875	6	15	100	15	5	20	20
BLM159-07	15.875	7	15	100	15	5	20	20
BLM16-04	16	4	15	100	15	5	15	15
BLM16-05	16	5	15	100	15	5	15	15
BLM16-06	16	6	15	100	15	5	20	20
BLM16-07	16	7	15	100	15	5	20	20
BLM19-04	19.05	4	18	100	18	5	15	15
BLM19-05	19.05	5	18	100	18	5	15	15
BLM19-06	19.05	6	18	100	18	5	20	20
BLM19-07	19.05	7	18	100	18	5	20	20
BLM20-04	20	4	13	100	19	5	15	15
BLM20-05	20	5	14	100	19	5	15	15
BLM20-06	20	6	15	100	19	5	20	20
BLM20-07	20	7	16	100	19	5	20	20
BLM22-04	22	4	13	125	21	5	15	15
BLM22-05	22	5	14	125	21	5	15	15
BLM22-06	22	6	15	125	21	5	20	20
BLM22-07	22	7	16	125	21	5	20	20
BLM25-04	25	4	13	125	24	5	15	15
BLM25-05	25	5	14	125	24	5	15	15
BLM25-06	25	6	15	125	24	5	20	20
BLM25-07	25	7	16	125	24	5	20	20
BLM254-04	25.4	4	13	125	24	5	15	15
BLM254-05	25.4	5	14	125	24	5	15	15
BLM254-06	25.4	6	15	125	24	5	20	20
BLM254-07	25.4	7	16	125	24	5	20	20


SPARE PARTS



Designation	Clamping screw A	Clamping screw B, C	Wrench	Seal cap (Optional parts: inner screw)
BLM159, 16...	SSHM4-4	SSHM4-4	P-2	CA-16(M6)
BLM19-04	SSHM4-4	SSHM4-6	P-2	CA-16(M6)
BLM19-05, 06, 07	SSHM4-4	SSHM4-4	P-2	CA-16(M6)
BLM20-04, 05	SSHM4-4	SSHM4-6	P-2	CA-16(M6)
BLM20-06, 07	SSHM4-4	SSHM4-4	P-2	CA-16(M6)
BLM22-...	SSHM4-4	SSHM4-6	P-2	CA-16(M6)
BLM25-04, 05	SSHM4-4	SSHM4-8	P-2	CA-16(M6)
BLM25-06	SSHM4-4	SSHM4-8	P-2	CA-16(M6)
BLM25-07	SSHM4-4	SSHM4-6	P-2	CA-16(M6)
BLM254-04, 05, 06	SSHM4-4	SSHM4-8	P-2	CA-16(M6)
BLM254-07	SSHM4-4	SSHM4-6	P-2	CA-16(M6)

BLS sleeves

Sleeves for boring bars with square shank (regular length)



Designation	DCONWS	LF	H
BLS16-08	8	125	28
BLS16-10	10	125	28
BLS16-12	12	125	28


SPARE PARTS



Designation	Wrench
BLS16-...	P-3

BLS-C sleeves

Sleeves for boring bars with square shank (short type)




Designation	DCONWS	LF	H
BLS16-08C	8	100	28
BLS16-10C	10	100	28
BLS16-12C	12	100	28

SPARE PARTS





Designation	Wrench
BLS16-**C	P-3

BLM sleeves**Sleeves for boring bars with round shank**

Designation	DCONWS	DCONMS	LF	H	B
BLM19-08	8	19.05	100	18	18
BLM20-08	8	20	100	19	18
BLM22-08	8	22	125	21	21
BLM254-08	8	25.4	125	24	24
BLM25-08C	8	25	55	24	23
BLM25-10C	10	25	55	24	23
BLM25-12C	12	25	55	24	23

SPARE PARTS

Designation	Wrench
BLM...	P-2.5





BLC sleeves**Standard Sleeves for boring bars with round shank**




Designation	DCONWS	LB	LF	DCONMS
BLC40-8	8	73	13	40
BLC40-10	10	73	13	40
BLC40-12	12	73	13	40
BLC40-16	16	73	13	40
BLC32-8C	8	45	20	32
BLC32-10C	10	45	20	32
BLC32-12C	12	45	20	32
BLC40-8C	8	55	13	40
BLC40-10C	10	55	13	40
BLC40-12C	12	55	13	40
BLC40-16C	16	55	13	40

SPARE PARTS

Designation	Wrench
BLC40-8	P-3
BLC40-1...	P-4
BLC32-8C	P-3
BLC32-1°C	P-4
BLC40-8C	P-3
BLC40-1°C	P-4

PRACTICAL EXAMPLES

Workpiece type		Machine parts	Automotive parts
Toolholder		A16Q-STUPR1103-D180	A12M-SDUCR07-D160
Insert		TPMT110308-PS	DCMT070204-PS
Grade		T6130	GT9530
Workpiece material		SUS304 (X5CrNi18-9)	S45C (C45)
			
Cutting conditions	Cutting speed: V_c (m/min)	300	170
	Feed : f (mm/rev)	0.25	0.15
	Depth of cut : a_p (mm)	1.5	0.25
	Coolant	Water soluble (External supply)	Water soluble (Internal supply)
Results		 When competitor's tools are used, inserts often fractured due to chip re-cutting and tool life is unstable. With excellent chip control, the Stream Jet Bar excels in chip control and eliminates unexpected insert breakage caused by chip re-cutting and delivers consistent tool life. The tool also disposes of chip tangling and gives outstanding chip evacuation when taper boring.	 Compared with the previously used competitor's tool, the tool life was increased by 50 % and the surface finish was also improved. Even when machining the small diameter ($\phi 17$) portion, chip control was improved.

Workpiece type		Machine parts	Automotive parts
Toolholder		E20S-SDUCR11-D270	A12M-SDUPL07-D180-P
Insert		DCMT11T304-PS	DPMT070204-PS
Grade		T9215	T9215
Workpiece material		S35C (C35)	S45C (C45)
			
Cutting conditions	Cutting speed: V_c (m/min)	70 - 160	130
	Feed : f (mm/rev)	0.12 - 0.2	0.1
	Depth of cut : a_p (mm)	1.0	1.5
	Coolant	Water soluble (Internal supply)	Water soluble (External supply)
Results		 Compared with a competitor chipbreaker tool for medium cutting, the PS-type chipbreaker improved chip control. Under stable machining, the Stream Jet Bar improved chip evacuation and eliminated insert fracturing caused by chip re-cutting. The result is improved tool life and surface finish.	Chattering was a common issue with the competitor's tool. JetStreamBar and DPMT insert significantly reduced chatter, improving surface finish quality.

Tungaloy Corporation (Head office)

11-1 Yoshima-Kogyodanchi
Iwaki-city, Fukushima, 970-1144 Japan
Phone: +81-246-36-8501
Fax: +81-246-36-8542
www.tungaloy.co.jp

Tungaloy America, Inc.

3726 N Ventura Drive
Arlington Heights, IL 60004, U.S.A.
Phone: +1-888-554-8394
Fax: +1-888-554-8392
www.tungaloyamerica.com

Tungaloy Canada

432 Elgin St. Unit 3
Brantford, Ontario N3S 7P7, Canada
Phone: +1-519-758-5779
Fax: +1-519-758-5791
www.tungaloy.co.jp/ca

Tungaloy de Mexico S.A.

C Los Arellano 113,
Parque Industrial Siglo XXI
Aguascalientes, AGS, Mexico 20290
Phone: +52-449-929-5410
Fax: +52-449-929-5411
www.tungaloy.com.mx

Tungaloy do Brasil Ltda.

Avd. Independencia N4158 Residencial Flora
13280-000 Vinhedo, São Paulo, Brasil
Phone: +55-19-38262757
Fax: +55-19-38262757
www.tungaloy.com.br

Tungaloy Germany GmbH

An der Alten Ziegelei 1
D-40789 Monheim, Germany
Phone: +49-2173-90420-0
Fax: +49-2173-90420-19
www.tungaloy.de

Tungaloy France S.A.S.

ZA Courtaboeuf - Le Rio
1 rue de la Terre de feu
F-91952 Courtaboeuf Cedex, France
Phone: +33-1-6486-4300
Fax: +33-1-6907-7817
www.tungaloy.fr

Tungaloy Italia S.r.l.

Via E. Andolfato 10
I-20126 Milano, Italy
Phone: +39-02-252012-1
Fax: +39-02-252012-65
www.tungaloy.it

Tungaloy Czech s.r.o.

Turanka 115
CZ-627 00 Brno, Czech Republic
Phone: +420-532 123 391
Fax: +420-532 123 392
www.tungaloy.cz

Tungaloy Ibérica S.L.

C/Miquel Servet, 43B, Nau 7
Pol. Ind. Bufalvent
ES-08243 Manresa (BCN), Spain
Phone: +34 93 113 1360
Fax: +34 93 876 2798
www.tungaloy.es

Tungaloy Scandinavia AB

Bultgatan 38
442 40 Kungälv, Sweden
Phone: +46-462119200
www.tungaloy.se

Tungaloy Rus, LLC

115432, Russian Federation, Moscow,
Andropova avenue., h.18, bld.7, flt. 11,
office 3.
Phone: +7-499-683-01-80/81
www.tungaloy.co.jp/ru

Tungaloy East LLC

620075, Russian Federation, Sverdlovsk
Region, Ekaterinburg, Mamina-Sibiryaka str.,
bldg. 101, room 202
Phone: +7-343-286-48-23/24
Fax: +7-912-284-91-69
www.tungaloy.co.jp/ru

Tungaloy Polska Sp. z o.o.

ul. Genewska 24
03-963 Warszawa, Poland
Phone: +48-22-617-0890
Fax: +48-22-617-0890
www.tungaloy.co.jp/pl

Tungaloy U.K. Ltd

The Technology Centre,
Wolverhampton Science Park
Glaisher Drive, Wolverhampton
West Midlands WV10 9RU, UK
Phone: +44 121 4000 231
Fax: +44 121 270 9694
www.tungaloy.co.jp/uk
salesinfo@tungaloyuk.co.uk

Tungaloy Hungary Kft

Erzsébet királyné útja 125
H-1142 Budapest, Hungary
Phone: +36 1 781-6846
Fax: +36 1 781-6866
www.tungaloy.co.jp/hu
info@tungaloytools.hu

Tungaloy Turkey

Dudullu, OSB 4. Cad No:4
34776 Umraniye Istanbul, TURKEY
Phone: +90 216 540 04 67
Fax: +90 216 540 04 87
www.tungaloy.com.tr
info@tungaloy.com.tr

Tungaloy Benelux b.v.

Tjalk 70
NL-2411 NZ Bodegraven, Netherlands
Phone: +31 172 630 420
Fax: +31 172 630 429
www.tungaloy-benelux.com

Tungaloy Croatia

Josipa Kozarca 4
10432 Bregana, Croatia
Phone: +385 1 3326 604
Fax: +385 1 3327 683
www.tungaloy.hr

Tungaloy Cutting Tool (Shanghai) Co., Ltd.

Rm No 401 No.88 Zhabei
Jiangchang No.3 Rd
Shanghai 200436, China
Phone: +86-21-3632-1880
Fax: +86-21-3621-1918
www.tungaloy.co.jp/tcts

Tungaloy Cutting Tool (Thailand) Co., Ltd.

Interlink tower 4th Fl.
1858/5-7 Bangna-Trad Road
km.5 Bangna, Bangkok 10260
Thailand
Phone: +66-2-751-5711
Fax: +66-2-751-5715
www.tungaloy.co.th

Tungaloy Singapore (Pte.), Ltd.

62 Ubi Road 1, #06-11 Oxley BizHub 2
Singapore 408734
Phone: +65-6391-1833
Fax: +65-6299-4557
www.tungaloy.co.jp/tspl

Tungaloy Vietnam

LE 04-38, Lexington Residence
67 Mai Chi Tho, Dist. 2,
Ho Chi Minh City, Vietnam
Phone: +84-8-37406660
Fax: +84-8-37406662
www.tungaloy.co.jp/vsp

Tungaloy India Pvt. Ltd.

Indiabulls Finance Centre,
Unit # 902-A, 9th Floor,
Tower 1, Senapati Bapat Marg,
Elphinstone Road (West),
Mumbai - 400013, India
Phone: +91-22-6124-8804
Fax: +91-22-6124-8899
www.tungaloy.co.jp/in

Tungaloy Korea Co., Ltd

#1312, Byucksan Digital Valley 5-cha
Beotkkot-ro 244, Geumcheon-gu
153-788 Seoul, Korea
Phone: +82-2-2621-6161
Fax: +82-2-6393-8952
www.tungaloy.co.jp/kr

Tungaloy Malaysia Sdn Bhd

50 K-2, Kelana Mall, Jalan SS6/14
Kelana Jaya, 47301
Petaling Jaya, Selangor Darul Ehsan
Malaysia
Phone: +603-7805-3222
Fax: +603-7804-8563
www.tungaloy.co.jp/my

Tungaloy Australia Pty Ltd

PO Box 2232, Rowville,
Victoria 3178, Australia
Phone: +61-3-9755-8147
Fax: +61-3-9755-6070
www.tungaloy.com.au

PT. Tungaloy Indonesia

Kompleks Grand Wisata Block AA-10 No.3-5
Cibitung
Bekasi 17510, Indonesia
Phone: +62-21-8261-5808
Fax: +62-21-8261-5809
www.tungaloy.co.jp/id



www.tungaloy.com

follow us at:

facebook.com/tungaloyjapan

twitter.com/tungaloyjapan

To see this product in action visit:

Tung-TV

www.youtube.com/tungaloycorporation

Distributed by:



DOWNLOAD
Dr. Carbide App



FIND US ON THE CLOUD!
machiningcloud.com



Available on the
App Store



GET IT ON
Google play



AS9100 Certified
78006
2015.11.04
ISO14001 Certified
EC97J1123
1997.11.26

Produced from Recycled paper

Apr. 2022 (TJ)