

ToolLine



For more information

Tooling system TUNGSHRINK

Tungaloy Report No. 389S7-US

Introducing SHRINKIN induction units — easy-to-use shrink-fit technology for fast and reliable performance







TUNGSHRINK

New SHRINKIN induction heating technology offers fast performance and extremely reliable precision

Features

Model AP

- Easy-to-use shrink-fit machine with automatic heating program
- Quick cooling and drying system requiring no more than 30 sec.
- Serviceable for carbide and HSS tools
- User-friendly control panel design
- Compatible to Tungaloy's SRKIN and SRK toolholders (HSS tools can be set in SRKIN holders only.)




| Tool Mounting Range | ø1/8"- 1 1/4" (carbide) / ø1/4"- 1 1/4" HSS Only in SRKIN holders |
|-----------------------------------|---|
| Maximum Holder Height | 15.748" |
| Output | 14.75 HP (11 kW) |
| Electrical Supply | 480V / 15A / 60 Hz - US |
| Dimensions (Width, Depth, Height) | 31.496" x 22.047" x 67.716" |
| Weight Excluding Lubricant | 265 lb |



Model BS

- Table-top model, portable design
- With air cooling
- Available for carbide tools only with clamping range from 1/8" 1 1/4"
- Easy input of shrink parameters by scanning bar codes
- Compatible for Tungaloy's SRKIN and SRK toolholders



| Tool Mounting Range | ø 1/8" - 1 1/4" (carbide) |
|-----------------------------------|-----------------------------|
| Maximum Holder Height | 15.748" |
| Output | 10.73 HP (8 kW) |
| Electrical Supply | 480V / 15A / 60 Hz - US |
| Dimensions (Width, Depth, Height) | 12.599" x 15.748" x 33.071" |
| Weight Excluding Lubricant | 44 lb |





Induction Heating Unit for Thermal Shrink Tool Chucking



Designation

INDN AP UNIT US

480V / 15A / 60Hz





INDN BS UNIT US

SHRINKIN Induction Heating Unit for Shrink Tool Chucking.



Designation

INDN BS UNIT US


480V / 15A / 60Hz






INDN AP DISC/SPLIT

Induction Coil Stop Disc AP Unit





| Designation | Туре | DMIN | DMAX | Clamping diameter | Included or Sold separately | Fig. |
|--------------------------|------|-------|-------|---------------------------|--------------------------------|-------------|
| INDN AP DISC 3-5 #0 | AP | 0.118 | 0.197 | 0.118 - 0.197 / SRK 0.236 | Included | 2 |
| INDN AP DISC 6-12 #1 | AP | 0.236 | 0.472 | 0.236 - 0.472 | Included | 2 |
| INDN AP DISC 14-20 #2 | AP | 0.551 | 0.866 | 0.551 - 0.866 | Included | 2 |
| INDN AP DISC 25-32 #3 | AP | 0.984 | 1.260 | 0.984 - 1.260 | Included | 2 |
| INDN AP DISC SKR3-5 #5 | AP | 0.118 | 0.197 | SRK 0.118 - 0.197 | Included | 2 |
| INDN AP DISC SKR8 #8 | AP | 0.315 | 0.315 | SRK 0.315 | Included | 2 |
| INDN AP DISC SKR12 #12 | AP | 0.394 | 0.472 | SRK 0.394 - 0.472 | Included | 2 |
| INDN AP SPLIT #0 | AP | 0.118 | 0.197 | 0.118 - 0.197 | Sold separately | 1 |
| INDN AP SPLIT #1 | AP | 0.236 | 0.472 | 0.236 - 0.472 | Sold separately | 1 |
| INDN AP SPLIT #2 | AP | 0.551 | 0.866 | 0.551 - 0.866 | Sold separately | 1 |
| INDN AP SPLIT #3 | AP | 0.984 | 1.260 | 0.984 - 1.260 | Sold separately | 1 |
| INDN AP DISC SHORT 12-22 | AP | 0.472 | 0.866 | Short 0.472 - 0.866 | Sold separately | 2 |
| INDN BS DISC 6-8 #1 | BS | 0.236 | 0.315 | 0.236 - 0.315 | Included | 2 |
| INDN BS DISC 10-14 #2 | BS | 0.394 | 0.551 | 0.394 - 0.551 | Included | 2 |
| INDN BS DISC 16-18 #3 | BS | 0.630 | 0.709 | 0.630 - 0.709 | Included | 2 |
| INDN BS DISC 20 #4 | BS | 0.787 | 0.787 | 0.787 | Included | 2 |
| INDN BS DISC 25-32 #5 | BS | 0.984 | 1.260 | 0.984 - 1.260 | Included | 2 |
| INDN BS DISC SRK3 #6 | BS | 0.118 | 0.118 | 0.118 | Sold separately | 2 |
| INDN BS DISC SRK4 #7 | BS | 0.157 | 0.157 | SRK 0.157 | Sold separately | 2 |
| INDN BS DISC SRK5 #8 | BS | 0.197 | 0.197 | SRK 0.197 | Sold separately | 2 |
| INDN BS DISC SRK6 #9 | BS | 0.236 | 0.236 | SRK 0.236 | Sold separately | 2 |
| INDN BS DISC SRK8 #10 | BS | 0.315 | 0.315 | SRK 0.315 | Sold separately | 2 |
| INDN BS DISC SRK10 #11 | BS | 0.394 | 0.394 | SRK 0.394 | Sold separately | 2 |
| INDN BS DISC SRK12 #12 | BS | 0.472 | 0.472 | SRK 0.472 | Sold separately | 2 |
| | | | | | | (Unit-Inch) |


(Unit: Inch)

TUNGSHRINK



INDN SETTING DISC

Height setting discs metric




| Designation | Туре | BD | DCONMS | Tool diameter | Included or Sold separately |
|-------------------------|---------|-------|--------|---------------|--------------------------------|
| INDN SETTING DISC 1/8 | AP / BS | 0.640 | 0.125 | 1/8 | Sold separately |
| INDN SETTING DISC 3/16 | AP / BS | 0.640 | 0.187 | 3/16 | Sold separately |
| INDN SETTING DISC 1/4 | AP / BS | 0.640 | 0.250 | 1/4 | Sold separately |
| INDN SETTING DISC 5/16 | AP / BS | 0.800 | 0.313 | 5/16 | Sold separately |
| INDN SETTING DISC 3/8 | AP / BS | 0.800 | 0.375 | 3/8 | Sold separately |
| INDN SETTING DISC 1/2 | AP / BS | 1.000 | 0.500 | 1/2 | Sold separately |
| INDN SETTING DISC 5/8 | AP / BS | 1.200 | 0.625 | 5/8 | Sold separately |
| INDN SETTING DISC 3/4 | AP / BS | 1.340 | 0.750 | 3/4 | Sold separately |
| INDN SETTING DISC 1.000 | AP/BS | 1.540 | 1.000 | 1 | Sold separately |
| INDN SETTING DISC 1 1/4 | AP / BS | 1.970 | 1.250 | 1 1/4 | Sold separately |

(Unit: Inch)



INDN AP AD

Tool holder adapter AP unit




| Designation | Туре | Suitable tool holder | d2 | Included or Sold separately |
|----------------|------|-------------------------|-------|-----------------------------|
| INDN AP AD 32 | AP | HSK32 | 1.260 | Sold separately |
| INDN AP AD 40 | AP | HSK40 / C4 | 1.575 | Sold separately |
| INDN AP AD 50 | AP | HSK50 / C5 / #30 | 1.968 | Sold separately |
| INDN AP AD 63 | AP | HSK63 / C6 / #40 / KM63 | 2.480 | Sold separately |
| INDN AP AD 80 | AP | HSK80 / C8 / #45 | 3.150 | Sold separately |
| INDN AP AD 100 | AP | HSK100 / C10 / #50 | 3.937 | Sold separately |

(Unit: Inch)



INDN BS AD HSK

Tool holder adapter BS unit



| Designation | Туре | Suitable tool holder | d2 | Included or Sold separately |
|----------------------|------|----------------------|-------|-----------------------------|
| INDN BS AD HSK 25 | BS | HSK25 | 0.984 | Sold separately |
| INDN BS AD HSK 32 | BS | HSK32 | 1.260 | Sold separately |
| INDN BS AD HSK 40 | BS | HSK40 | 1.575 | Sold separately |
| INDN BS AD HSK 50 | BS | HSK50 | 1.968 | Sold separately |
| INDN BS AD HSK 63 | BS | HSK63 | 2.480 | Sold separately |
| INDN BS AD HSK 80 | BS | HSK80 | 3.150 | Sold separately |
| INDN BS AD HSK 100 | BS | HSK100 | 3.937 | Sold separately |
| INDN BS AD TAPER #30 | BS | #30 | 1.968 | Sold separately |
| INDN BS AD TAPER #40 | BS | #40 | 2.480 | Sold separately |
| INDN BS AD TAPER #50 | BS | #50 | 3.937 | Sold separately |
| INDN BS AD C3 | BS | C3 | 1.260 | Sold separately |
| INDN BS AD C4 | BS | C4 | 1.575 | Sold separately |
| INDN BS AD C5 | BS | C5 | 1.968 | Sold separately |
| INDN BS AD C6 | BS | C6 | 2.480 | Sold separately |
| INDN BS AD C8 | BS | C8 | 3.150 | Sold separately |

(Unit: Inch)

PARTS

| Appearance | Designation | Туре | Included or Sold separately |
|------------|-------------------------|-------|-----------------------------|
| | INDN CLAMP RING | AP/BS | Included |
| # Th. | IND THERMIC GLOVES | AP/BS | Included |
| | COOLANT SYNERGY 905 | АР | Included |
| | INDN AP COIL LIMIT STOP | AP | Sold separately |
| - | INDN AP SERVICE PUMP | АР | Sold separately |

Tungaloy-NTK America Inc.

United States

3726 N Ventura Drive, Arlington Heights, IL 60004, U.S.A.

Inside Sales: +1-888-554-8394 Technical Support: +1-888-554-8391

Fax: +1-888-554-8392 www.tungaloy.com/us

Canada

432 Elgin St. Unit 3, Brantford, Ontario N3S 7P7, Canada Phone: +1-519-758-5779 Fax: +1-519-758-5791

www.tungaloy.com/ca

Mexico

C Los Arellano 113, Parque Industrial Siglo XXI Aguascalientes, AGS, Mexico 20290 Phone: +52-449-929-5410 Fax: +52-449-929-5411 www.tungaloy.com/mx



Scan for instant web access



tungaloy.com/us

follow us at:

facebook.com/tungaloyamerica instagram.com/tungaloyamerica linkedin.com/company/tungaloy-america To see Tungaloy products in action visit:



www.youtube.com/tungaloycorporation

Distributed by:







AS9100 Certified 78006 2015.11.04 ISO 14001 Certified EC97J1123 1997.11.26