



Profile milling cutter

FIXRMILL


Tungaloy Report No. 418S2-G

Upgrading FixRMill by expanding **Size R5 and R8 insert lines**




Accurate and secure clamping

- The anti-rotation system securely keeps the inserts locked in place and prevents them from moving in the pockets during machining, ensuring tool reliability and accurate indexing over various applications.



Applications capabilities



- High productive cutter with close pitch design




Inserts per diameter density comparisons: FixRMILL vs conventional round insert cutter

Tool diameter DCX (mm)		New FIXRMILL close pitched	Conventional round insert cutter
R5	ø50	6	5
R6	ø63	7	6
R8	ø66	6	5


Two types of inserts

- Both inserts can be clamped in the same pocket
- Inserts can be selected based on the required depth of cut for best cost per edge



RQMT****ENC8-MM

	For 8 indexes	For 4 indexes
R5	DOC ≤ 1.2 mm	DOC ≤ 5 mm
R6	DOC ≤ 1.4 mm	DOC ≤ 6 mm
R8	DOC ≤ 2 mm	DOC ≤ 8 mm




RQMT****ENC6-MM

	For 6 indexes	For 3 indexes
R5	DOC ≤ 2.2 mm	DOC ≤ 5 mm
R6	DOC ≤ 2.6 mm	DOC ≤ 6 mm
R8	DOC ≤ 3.5 mm	DOC ≤ 8 mm


TOOL LIFE

P Carbon steel
S55C / C55 (200HB)




Cutter : ERRQ10M032C32.0R05 (DCX = 32 mm, CICT = 5)
 Insert : RQMT10T3ENC8-MM AH3135
 Cutting speed : $V_c = 150$ m/min
 Feed per tooth : $f_z = 0.6$ mm/t
 Depth of cut : $a_p = 1.2$ mm
 Width of cut : $a_e = 19$ mm
 Coolant : Dry
 Overhang length: 70 mm
 Machine : Vertical M/C, BT40
 Performed with all inserts on the cutter

P Alloy steels
SCM440 / 42CrMo4 (270HB)




Cutter : TRRQ16M063B22.0R06 (DCX = 63 mm, CICT = 6)
 Insert : RQMT1605ENC8-MM AH3135
 Cutting speed : $V_c = 150$ m/min
 Feed per tooth : $f_z = 0.6$ mm/t
 Depth of cut : $a_p = 2$ mm
 Width of cut : $a_e = 38$ mm
 Coolant : Dry
 Overhang length: 100 mm
 Machine : Vertical M/C, BT50
 Performed with only one insert on the cutter

P Plastic mold steel
NAK80 (40HRC)



Cutter : TRRQ12M050B22.0R05 (DCX = 50 mm, CICT = 5)
 Insert : RQMT1204ENC6-MM AH3135
 Cutting speed : $V_c = 140$ m/min
 Feed per tooth : $f_z = 0.3$ mm/t
 Depth of cut : $a_p = 1.5$ mm
 Width of cut : $a_e = 20$ mm
 Coolant : Dry
 Overhang length: 150 mm
 Machine : Horizontal M/C, BT40
 Performed with only one insert on the cutter

M Austenitic stainless steel
SUS304 / X5CrNi18-9 (160HB)




Cutter : TRRQ12M050B22.0R06 (DCX = 50 mm, CICT = 6)
 Insert : RQMT1204ENC8-MM AH3135
 Cutting speed : $V_c = 75$ m/min
 Feed per tooth : $f_z = 0.3$ mm/t
 Depth of cut : $a_p = 1$ mm
 Width of cut : $a_e = 3$ mm
 Coolant : Dry
 Overhang length: 150 mm
 Machine : Vertical M/C, HSK100
 Performed with all inserts on the cutter

BORE TYPE

TRRQ

Radius mill with anti-rotation system

GAMP = +4° ~ +5°, GAMF = -4° ~ -3°



	Designation	APMX	DCX	CICT	DC	DCSFMS	DCONMS	LF	CBDP	KWW	b	WT(kg)	Air hole	Insert
New	TRRQ10M040B16.0R06	5	40	6	30	34	16	40	18	8.4	5.6	0.18	With	RQMT10...
New	TRRQ10M050B22.0R06	5	50	6	40	45	22	40	20	10.4	6.3	0.31	With	RQMT10...
New	TRRQ10M050B22.0R07	5	50	7	40	45	22	40	20	10.4	6.3	0.32	With	RQMT10...
New	TRRQ10M052B22.0R06	5	52	6	42	45	22	40	20	10.4	6.3	0.33	With	RQMT10...
	TRRQ12M040B16.0R04 ⁽¹⁾	6	40	4	28	34	16	40	24	8.4	5.6	0.16	With	RQMT12...
	TRRQ12M050B22.0R05	6	50	5	38	45	22	40	20	10.4	6.3	0.27	With	RQMT12...
	TRRQ12M050B22.0R06	6	50	6	38	45	22	40	20	10.4	6.3	0.26	With	RQMT12...
	TRRQ12M052B22.0R05	6	52	5	40	45	22	40	20	10.4	6.3	0.29	With	RQMT12...
	TRRQ12M063B22.0R06	6	63	6	51	50	22	40	20	10.4	6.3	0.44	With	RQMT12...
	TRRQ12M063B22.0R07	6	63	7	51	50	22	40	20	10.4	6.3	0.42	With	RQMT12...
	TRRQ12M080B27.0R06	6	80	6	68	56	27	50	22	12.4	7	0.88	With	RQMT12...
New	TRRQ16M052B22.0R05	8	52	5	36	45	22	40	20	10.4	6.3	0.3	With	RQMT16...
New	TRRQ16M063B22.0R05	8	63	5	47	50	22	40	20	10.4	6.3	0.44	With	RQMT16...
New	TRRQ16M063B22.0R06	8	63	6	47	50	22	40	20	10.4	6.3	0.45	With	RQMT16...
New	TRRQ16M066B27.0R06	8	66	6	50	56	27	50	22	12.4	7	0.61	With	RQMT16...
New	TRRQ16M080B27.0R07	8	80	7	64	56	27	50	22	12.4	7	0.8	With	RQMT16...

(1) Always use the dedicated shell locking bolt # SRPS118-0416 when assembling the cutter on the arbor. See page 10 for the instruction for the cutter-arbor assembly. Coolant needs to be supplied from the end of the arbor inlay. Coolant cannot be supplied from the shell locking bolt.

SPARE PARTS

Designation	Clamping screw	Torx bit	Grip	Shell locking bolt 1	Shell locking bolt 2
TRRQ10M040B16.0R06	CSPB-3.5S	BLD IP15/S7	H-TB2W	FSHM8-30H	-
TRRQ10M050 - 052...	CSPB-3.5S	BLD IP15/S7	H-TB2W	CM10X30H	-
TRRQ12M040B16.0R04	CSPB-4S	BLD IP15/S7	H-TB2W	-	SRPS118-0416
TRRQ12M050 - 063...	CSPB-4S	BLD IP15/S7	H-TB2W	CM10X30H	-
TRRQ12M080B27.0R06	CSPB-4S	BLD IP15/S7	H-TB2W	CM12X30H	-
TRRQ16M052 - 063...	CSPB-5	BLD IP20/S7	H-TB2W	FSHM10-40H	-
TRRQ16M066 - 080...	CSPB-5	BLD IP20/S7	H-TB2W	CM12X30H	-


*Recommended clamping torque (N·m): CSPB-3.5S, CSPB-4S = 3.5, CSPB-5 = 5

SHANK TYPE

ERRQ

Radius endmill with anti-rotation system, shank type

GAMP = +1.6° ~ +5°, GAMF = -6.2° ~ -3°



	Designation	APMX	DCX	CICT	DC	DCONMS	LF	LH	LS	WT(kg)	Air hole	Insert
New	ERRQ10M032C32.0R05	5	32	5	22	32	150	70	80	0.78	With	RQMT10...
New	ERRQ12M032C32.0R03	6	32	3	20	32	150	50	100	0.81	With	RQMT12...
	ERRQ12M040C32.0R04	6	40	4	28	32	150	50	100	0.84	With	RQMT12...

SPARE PARTS



Designation	Clamping screw	Torx bit	Grip
ERRQ10M032C32.0R05	CSPB-3.5S	BLD IP15/S7	H-TB2W
ERRQ12M032 - 040	CSPB-4S	BLD IP15/S7	H-TB2W


*Recommended clamping torque (N·m): CSPB-3.5S, CSPB-4S = 3.5

MODULAR TYPE

HRRQ

Radius endmill with anti-rotation system, modular type (TungFlex)

GAMP = +1.6° ~ +5°, GAMF = -6.2° ~ -3°



	Designation	APMX	DCX	CICT	DC	OAL	LF	H	DCSFMS	CRKS	WT(kg)	Air hole	Insert
New	HRRQ10M032M16R05	5	32	5	22	63	40	22	28.8	M16	0.19	With	RQMT10...
New	HRRQ12M032M16R03	6	32	3	20	63	40	22	28	M16	0.17	With	RQMT12...
New	HRRQ12M040M16R05	6	40	5	28	63	40	22	28	M16	0.21	With	RQMT12...

SPARE PARTS




Designation	Clamping screw	Torx bit	Grip
HRRQ10M...	CSPB-3.5S	BLD IP15/S7	H-TB2W
HRRQ12M...	CSPB-4S	BLD IP15/S7	H-TB2W

*Recommended clamping torque (N·m): CSPB-3.5S, CSPB-4S = 3.5

SM

Steel modular shank




Designation	CRKS	DCONMS	LF	LB	BD	BHTA
SM16-L95-C32	M16	32	95	35	29	1.7°
SM16-L230-C32	M16	32	230	50	29	1.8°

e-catalog



SM-C-H

Carbide modular shank




Designation	CRKS	DCONMS	LF	LB	LS	BD
SM16-L100-40-C32-C-H	M16	32	100	40	58.5	29
SM16-L150-80-C32-C-H	M16	32	150	80	68.5	29
SM16-L200-100-C32-C-H	M16	32	200	100	98.5	29
SM16-L200-140-C32-C-H	M16	32	200	140	58.5	29
SM16-L250-130-C32-C-H	M16	32	250	130	118.5	29
SM16-L250-180-C32-C-H	M16	32	250	180	68.5	29
SM16-L300-180-C32-C-H	M16	32	300	180	118.5	29
SM16-L300-230-C32-C-H	M16	32	300	230	68.5	29
SM16-L350-230-C32-C-H	M16	32	350	230	118.5	29
SM16-L350-280-C32-C-H	M16	32	350	280	68.5	29

e-catalog



BT-RSG (Screw clamping head holder)

TungFlex modular tooling system with BT shank




Designation	DCONWS	LSC	LSCN	BD	LF	LPR	LH	BD2	BD3	WT (kg)	G
BT50-RSG 16-140-M 25	17	25	6	29	140	25	115	52	54	5.4	M16
BT50-RSG 16-165-M 50	17	25	6	29	165	50	115	52	54	5.6	M16
BT50-RSG 16-190-M 75	17	25	6	29	190	75	115	52	54	5.8	M16
BT50-RSG 16-215-M100	17	25	6	29	215	100	115	52	54	6	M16
BT50-RSG 16-240-M125	17	25	6	29	240	125	115	52	54	6.2	M16

e-catalog




INSERTS

RQMT...C8-MM



RQMT...C6-MM



	P	M	K	N	S	H
Steel	★					
Stainless	★					
Cast iron			★			
Non-ferrous						
Superalloy	★	★				
Hard materials	☆	☆				

★ : First choice
☆ : Second choice

Designation	RE	APMX	Coated		INSD	S
			AH3135	AH8015		
RQMT10T3ENC8-MM	5	5	●	●	10	3.97
RQMT10T3ENC6-MM	5	5	●	●	10	3.97
RQMT1204ENC8-MM	6	6	●	●	12	4.76
RQMT1204ENC6-MM	6	6	●	●	12	4.76
RQMT1605ENC8-MM	8	8	●	●	16	5.61
RQMT1605ENC6-MM	8	8	●	●	16	5.61

● : New product
● : Line up

GRADES

AH3135 **P** **M** **S** **H**

- PVD grade for high fracture resistance
- Most suitable for steel, stainless steel, and titanium alloy in general cutting parameters


AH8015 **K** **S** **H**

- Incorporates a hard coating layer and carbide substrate
- Strong resistance to wear, heat, and built-up edge. Ideal for machining cast iron, heat-resistant alloy, and hardened steel

STANDARD CUTTING CONDITIONS

ISO	Workpiece materials	Hardness	Grades	Cutting speed Vc (m/min)	Feed per tooth: fz (mm/t)			
					RQMT10...	RQMT12...	RQMT16...	
P	Low carbon steel S15C, etc. C15E4, etc.	- 200HB	AH3135	100 - 300				
	Carbon steel and alloy steel S55C, SCM440, etc. C55, 42CrMo4, etc.	- 300HB	AH3135	100 - 250	ap = 5 mm : 0.1 - 0.3 ap = 2 mm : 0.15 - 0.6 ap = 1 mm : 0.2 - 0.8	ap = 6 mm : 0.1 - 0.3 ap = 2 mm : 0.15 - 0.6 ap = 1 mm : 0.2 - 0.8	ap = 8 mm : 0.1 - 0.3 ap = 2 mm : 0.15 - 0.7 ap = 1 mm : 0.2 - 1	
	Prehardened steel NAK80, PX5, etc.	30 - 40HRC	AH3135	100 - 200				
M	Austenitic stainless steel SUS304, SUS316, etc. X5CrNi18-9, X5CrNiMo17-12-3, etc.	- 200HB	AH3135	100 - 200	ap = 5 mm : 0.1 - 0.25 ap = 2 mm : 0.15 - 0.5 ap = 1 mm : 0.2 - 0.65	ap = 6 mm : 0.1 - 0.25 ap = 2 mm : 0.15 - 0.5 ap = 1 mm : 0.2 - 0.65	ap = 8 mm : 0.1 - 0.25 ap = 2 mm : 0.15 - 0.55 ap = 1 mm : 0.2 - 0.8	
	Martensitic stainless steel SUS420J1, etc. X20Cr13, etc.	- 200HB	AH3135	100 - 300				
K	Grey cast iron FC250, etc. 250, etc.	150 - 250HB	AH8015	100 - 300	ap = 5 mm : 0.1 - 0.3 ap = 2 mm : 0.15 - 0.6 ap = 1 mm : 0.2 - 0.8	ap = 6 mm : 0.1 - 0.3 ap = 2 mm : 0.15 - 0.6 ap = 1 mm : 0.2 - 0.8	ap = 8 mm : 0.1 - 0.3 ap = 2 mm : 0.15 - 0.7 ap = 1 mm : 0.2 - 1	
	Ductile cast iron FCD400, FCD600, etc. 400-15S, 600-3, etc.	150 - 250HB	AH8015	80 - 250				
S	Titanium alloys Ti-6Al-4V, etc.	-	AH3135	30 - 60	ap = 5 mm : 0.08 - 0.2 ap = 2 mm : 0.12 - 0.4 ap = 1 mm : 0.15 - 0.6	ap = 6 mm : 0.08 - 0.2 ap = 2 mm : 0.12 - 0.4 ap = 1 mm : 0.15 - 0.6	ap = 8 mm : 0.08 - 0.2 ap = 2 mm : 0.1 - 0.2 ap = 1 mm : 0.15 - 0.8	
	Heat-resistant alloys Inconel718, etc.	-	AH8015	20 - 50	ap = 5 mm : 0.05 - 0.12 ap = 2 mm : 0.08 - 0.25 ap = 1 mm : 0.1 - 0.3	ap = 6 mm : 0.05 - 0.12 ap = 2 mm : 0.08 - 0.25 ap = 1 mm : 0.1 - 0.3	ap = 8 mm : 0.05 - 0.12 ap = 2 mm : 0.06 - 0.3 ap = 1 mm : 0.08 - 0.4	
H	Hardened steel	SKD61, etc. X40CrMoV5-1, etc.	40 - 50HRC	AH3135	50 - 150	ap = 5 mm : 0.05 - 0.12 ap = 2 mm : 0.08 - 0.25 ap = 1 mm : 0.1 - 0.3	ap = 5 mm : 0.05 - 0.12 ap = 2 mm : 0.08 - 0.25 ap = 1 mm : 0.1 - 0.3	ap = 5 mm : 0.05 - 0.12 ap = 2 mm : 0.08 - 0.25 ap = 1 mm : 0.1 - 0.3
		SKD11, etc. X153CrMoV12, etc.	50 - 60HRC	AH8015	50 - 70	ap = 5 mm : 0.03 - 0.1 ap = 2 mm : 0.05 - 0.12 ap = 1 mm : 0.05 - 0.15	ap = 5 mm : 0.03 - 0.1 ap = 2 mm : 0.05 - 0.12 ap = 1 mm : 0.05 - 0.15	ap = 5 mm : 0.03 - 0.1 ap = 2 mm : 0.05 - 0.12 ap = 1 mm : 0.05 - 0.15

APPLICATION RANGE




Designation	DCX	Max. depth of cut	Max. ramping angle	Max. plunging depth	Max. cutting width in plunging	Machining length for removing uncut portion	Min. machining diameter	Max. machining diameter	Max. cutting width engagement
		APMX	RMPX	A	W	L	øD1	øD2*	ae
New E/HRRQ10M032...	32	5	3.6°	1	5	23	48	63	25
New TRRQ10M040B16.0R06	40	5	5.4°	2.4	5	31	62	79	33
New TRRQ10M050B22....	50	5	3.8°	2.4	5	41	82	99	43
New TRRQ10M052B22.0R06	52	5	3.8°	2.4	5	43	86	103	45
New E/HRRQ12M032...	32	6	3°	0.8	6	21	47	63	24
T/ERRQ12M040...	40	6	5.1°	2.4	6	29	59	79	32
New HRRQ12M040M016R05	40	6	7°	2.6	6	29	59	79	32
TRRQ12M050B22.0...	50	6	3.6°	2.4	6	39	79	99	42
TRRQ12M052B22.0R05	52	6	3.4°	2.4	6	41	83	103	44
TRRQ12M063B22.0...	63	6	3°	2.4	6	52	105	125	55
TRRQ12M080B27.0R06	80	6	2.1°	2.4	6	69	139	159	72
New TRRQ16M052B22.0R05	52	8	4°	2	8	37	78	103	42
New TRRQ16M063B22.0...	63	8	6.6°	4.5	8	48	96	125	53
New TRRQ16M066B27.0R06	66	8	6.2°	4.5	8	51	102	131	56
New TRRQ16M080B27.0R07	80	8	4.6°	4.5	8	65	130	159	70

* For bottom hole

How to Assemble on the Arbor (For Cutter # TRRQ12M040B16.0R04)

Before assembly


- Ensure before assembly that the milling cutter, dedicated shell locking bolt, and arbor are present and of the right sizes. (Fig. ①)
- The screw end with the hex hole should be inserted in the cutter body; the screw end with no hole goes in the arbor. (Fig. ②)



Assembling the screw in the cutter body

- Insert the screw end with the hex hole into the cutter body. (Fig. ③)
- Turn the screw counterclockwise (left) until it stops. (Fig. ④)
- Ensure that 2 to 3 threads are visible from the top of the cutter body. (Fig. ⑤)

NOTE: Always insert the shell locking bolt from the bottom of the cutter. NEVER insert the screw into the top of the cutter body; this will damage the screw threads.






Assembling the cutter and arbor

- Place the cutter body on the arbor so that the drive keys on the arbor engage the grooves on the cutter body. (Fig. ⑥)
- Tighten the screw clockwise (right) to lock the cutter body onto the arbor. While doing so, ensure that the drive keys stay in contact with the grooves at all times. (Fig. ⑦)
- Tighten the screw until the cutter body flange face is flush with the arbor face. (Fig. ⑧)
- Ensure the cutter body does not rotate on the arbor to finish the assembly.

NOTE: Recommended torque for the screw: 8N·m



PRACTICAL EXAMPLES

Workpiece type		Mold	Generator part
Cutter		TRRQ12M050B22.0R05 (DCX = 50 mm, CICT = 5)	TRRQ12M050B22.0R06 (DCX = 50 mm, CICT = 6)
Insert		RQMT1204ENC8-MM	RQMT1204ENC8-MM
Grade		AH3135	AH3135
Workpiece material		S45C / C45	SUS304 / X5CrNi18-9
Cutting conditions			
Cutting speed: V_c (m/min)		125	75
Feed per tooth: f_z (mm/t)		1.25	0.3
Depth of cut : a_p (mm)		0.5	1
Width of cut : a_e (mm)		50	3
Machining		Profiling	Profiling
Coolant		Air	Air
Machine		Vertical M/C, BT50	Vertical M/C, HSK100
Results		 <p>No chipping Chipping</p> <p>The competitor's cutter resulted in edge chipping and could not complete the machining of one workpiece.</p> <p>FixRMill demonstrated no edge chipping and completed one workpiece thanks to its tough AH3135 grade inserts.</p>	<p>Due to a long overhang setup of 4xD and insecure anti-rotation feature, the competitor's cutter allowed the inserts to rotate during machining, yielding damage to the insert pockets and short cutter tool life.</p> <p>FixRMill prevented insert rotation thanks to its anti-rotation system, providing the cutter with security and long tool life.</p>
Workpiece type		Mold	Generator part
Cutter		ERRQ10M032C32.0R05 (DCX = 32 mm, CICT = 5)	TRRQ16M080B27.0R07 (DCX = 80 mm, CICT = 7)
Insert		RQMT10T3ENC8-MM	RQMT1605ENC8-MM
Grade		AH3135	AH3135
Workpiece material		SKD61 / X40CrMoV5-1	SUS430 / X6Cr17
Cutting conditions			
Cutting speed: V_c (m/min)		120	180
Feed per tooth: f_z (mm/t)		0.15	0.15
Depth of cut : a_p (mm)		3.5	0.2
Width of cut : a_e (mm)		15	45
Machining		Shoulder milling	Face milling
Coolant		Air	Air
Machine		Tower M/C, BT50	Vertical M/C, HSK63
Results		 <p>Productivity 4.2 times!</p> <p>FixRMill provided reduced cutting load and chatter-free machining, achieving 4.2 times productivity boost.</p>	 <p>Tool life 2.2 times!</p> <p>FixRMill, combined with fracture-resistant AH3135 grade inserts, provided 2.2 times tool life increase.</p>

Tungaloy Corporation (Head office)

11-1 Yoshima-Kogyodanchi
Iwaki-city, Fukushima 970-1144 Japan
Phone: +81-246-36-8501
Fax: +81-246-36-8542
www.tungaloy.co.jp

Tungaloy-NTK America Inc.

3726 N Ventura Drive
Arlington Heights, IL 60004, U.S.A.
Phone: +1-888-554-8394
Fax: +1-888-554-8392
www.tungaloy.com/us

Tungaloy Canada

432 Elgin St. Unit 3
Brantford, Ontario N3S 7P7, Canada
Phone: +1-519-758-5779
Fax: +1-519-758-5791
www.tungaloy.com/ca

Tungaloy-NTK De Mexico S.A.

C. Los Arellano 113,
Parque Industrial Siglo XXI
Aguascalientes, AGS, Mexico 20290
Phone: +52-449-929-5410
Fax: +52-449-929-5411
www.tungaloy.com/mx

Tungaloy-NTK do Brasil Ltda.

Avd. Independencia N4158 Residencial Flora
13280-000 Vinhedo, São Paulo, Brasil
Phone: +55-19-38262757
Fax: +55-19-38262757
www.tungaloy.com/br

Tungaloy-NTK Germany GmbH.

Katzbergstr. 3a
D-40764 Langenfeld, Germany
Phone: +49-2173-90420-0
Fax: +49-2173-90420-19
www.tungaloy.com/de

Tungaloy France s.a.s

Les Fjords
19 avenue de Norvège
91140 Villebon Sur Yvette, France
Phone: +33-1-6486-4300
Fax: +33-1-6907-7817
www.tungaloy.com/fr

Tungaloy Italia S.r.l.

Via E. Andolfato 10
I-20126 Milano, Italy
Phone: +39-02-252012-1
Fax: +39-02-252012-65
www.tungaloy.com/it

Tungaloy Czech s.r.o.

Turanka 115
CZ-627 00 Brno, Czech Republic
Phone: +420-532 123 391
Fax: +420-532 123 392
www.tungaloy.com/cz

Tungaloy Ibérica S.L.

C/Miquel Servet, 43B, Nau 7
Pol. Ind. Bufalvent
ES-08243 Manresa (BCN), Spain
Phone: +34 93 113 1360
www.tungaloy.com/es

Tungaloy Scandinavia AB

Bultgatan 38
442 40 Kungälv, Sweden
Phone: +46-462119200
Fax: +46-462119207
www.tungaloy.com/se

Tungaloy Rus, LLC

Andropova avenue, h.18/7,
11 floor, office 3, 115432,
Moscow, Russia
Phone: +7-499-683-01-80
Fax: +7-499-683-01-81
www.tungaloy.com/ru

Tungaloy Polska Sp. z o.o.

Ul. Irysowa 1, 55-040 Bielany
Wroclawskie, Poland
Phone: +48 607 907 237
www.tungaloy.com/pl

Tungaloy-NTK UK Ltd.

Suite 3, Pioneer House, Mill Street,
Cannock, WS11 0EF, UK
Phone: +44 121 4000 231
Fax: +44 121 270 9694
www.tungaloy.com/uk

Tungaloy Hungary Kft

Erzsébet királyné útja 125
H-1142 Budapest, Hungary
Phone: +36 1 781-6846
Fax: +36 1 781-6866
www.tungaloy.com/hu

Tungaloy Turkey

Serifali Mah.bayraktar Bulvari Kule Sk. No:26
34775 Umraniye / Istanbul / Turkey
Phone: +90 216 540 04 67
Fax: +90 216 540 04 87
www.tungaloy.com/tr

Tungaloy Benelux b.v.

Tjalk 70
NL-2411 NZ Bodegraven, Netherlands
Phone: +31 172 630 420
Fax: +31 172 630 429
www.tungaloy.com/nl

Tungaloy Croatia

Ulica bana Josipa Jelačića 87,
10430, Samobor, Croatia
Phone: +385 1 3326 604
Fax: +385 1 3327 683
www.tungaloy.com/hr

Tungaloy Cutting Tool (Shanghai) Co. Ltd.

Rm No 401 No.88 Zhabei
Jiangchang No.3 Rd
Shanghai 200436, China
Phone: +86-21-3632-1880
Fax: +86-21-3621-1918
www.tungaloy.com/cn

Tungaloy Cutting Tools Taiwan Co. Ltd.

9F, No.293, Zhongyang Rd,
Xinzhuang Dist, New Taipei City,
24251 Taiwan
Phone: +886-2-8521-9986
Fax: +886-2-8521-8935
www.tungaloy.com/tw

Tungaloy-NTK Cutting Tool (Thailand) Co.,Ltd.

Interlink tower 4th Fl.
1858/5-7 Bangna-Trad Road
km.5 Bangna, Bangna, Bangkok 10260
Thailand
Phone: +66-2-751-5711
Fax: +66-2-751-5715
www.tungaloy.com/th

Tungaloy Singapore (Pte.), Ltd.

62 Ubi Road 1, #06-11 Oxley BizHub 2
Singapore 408734
Phone: +65-6391-1833
Fax: +65-6299-4557
www.tungaloy.com/sg

Tungaloy Vietnam

LE04.38, Lexington Residence
67 Mai Chi Tho St., Dist. 2,
Ho Chi Minh City, Vietnam
Phone: +84-2837406660
www.tungaloy.com/sg

Tungaloy India Pvt. Ltd.

One International Center,
Unit # 902-A, 9th Floor,
Tower 1, Senapati Bapat Marg,
Elphinstone Road (West),
Mumbai 400013, India
Phone: +91-22-6124-8803
Fax: +91-22-6124-8899
www.tungaloy.com/in

Tungaloy Korea Co., Ltd

#1312, Byucksan Digital Valley 5-cha
Beotkkot-ro 244, Geumcheon-gu
153-788 Seoul, Korea
Phone: +82-2-2621-6161
Fax: +82-2-6393-8952
www.tungaloy.com/kr

Tungaloy Malaysia Sdn Bhd

50 K-2, Kelana Mall, Jalan SS6/14
Kelana Jaya, 47301
Petaling Jaya, Selangor Darul Ehsan
Malaysia
Phone: +603-7805-3222
Fax: +603-7804-8563
www.tungaloy.com/my

Tungaloy Australia Pty Ltd

Unit 68 1470 Ferntree Gully Road
Knoxfield 3180 Victoria, Australia
Phone: +61-3-9755-8147
Fax: +61-3-9755-6070
www.tungaloy.com/au

PT. Tungaloy Indonesia

Ruko Blok AA.10 No3&5, Grand Wisata,
Lambangjaya, Tambun Selatan, Bekasi,
17510 Indonesia
Phone: +62-21-8261-5808
Fax: +62-21-8261-5809
www.tungaloy.com/id



tungaloy.com

follow us at:

facebook.com/tungaloyjapan

twitter.com/tungaloyjapan

www.youtube.com/tungaloycorporation

Distributed by:



Tungaloy APP & SNS

FIND US ON THE CLOUD!
machingcloud.com



AS9100 Certified
78006
2015.11.04
ISO 14001 Certified
EC97J1123
1997.11.26